[LAB LOGO]

Test Report No.:	xx001		Page 1 of xx
		Issue Date:	DD/MM/YYYY

Manufacturer:	Applicant's Name Applicant's address			
Test item:	Passport Reader			
Identification:	(Model No.)	Serial No.:		
Receipt No.:		Date of receipt:		
Testing laboratory and its address:	Lab Name Lab address			
Test specification:	IS 13252 (Part 1): 2010 + IEC 60950-1: 2005 + A1:			
Test Result:	The test item passed / fail	led the test specification(s).		
Other Aspects: - Brief description or add	itional details could be given	by the labs here.		
This test report relates to the test sample submitted and list of documents attached.				

Tested by:	Approved by / Authorized Signatory:	Issued by:
(Name / Designation)	(Name / Designation)	(Name / Designation)
Date:	Date:	Date:

TEST REPORT

IS 13252 (Part 1): 2010 + A1: 2013+ A2: 2015 / IEC 60950-1: 2005 + A1: 2009 + A2: 2013 Information technology equipment - Safety -

Part 1: General requirements

"Passport Reader" Report Reference No..... xxxxxxxxx 001 Date of issue.....: (see cover page) Total number of pages (see cover page) Lab Name Testing Laboratory..... Address: Lab address Manufacturer's name Applicant's Name Address: Applicant's address Test specification: Standard....:: IS 13252 (Part 1): 2010 + A1: 2013+ A2:2015 / IEC 60950-1: 2005 + A1: 2009 +A2:2013 Compliance Report Test procedure: Non-standard test method.....: N/A Test Report Form No..... BIS_IT/PR_IS13252_V1.2 Test Report Form(s) Originator: Bureau of Indian Standards 03/06/2016 Master TRF..... Test item description **Passport Reader** Trade Mark: Model/Type reference: Ratings: Other Documents submitted.....: Please refer to Table – List of Attachments at Page No. xx

Tested by:	Approved by / Authorized Signatory:	Issued by:
(Name / Designation)	(Name / Designation)	(Name / Designation)
Date:	Date:	Date:

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 3 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Test Code	Description	Measurement/ testing	Total No. of tests	Total no. of applicable tests/ Req.	No. of tests/ Req. passed	Page No.
EL 2100	General Requirements	Components (CI.1.5)				
EL 2101	General Requirements	Power interface (Cl.1.6)				
EL 2102	Marking Requirements	Marking & instructions(Cl.1.7)				
EL 2103	Electrical safety	Protection from electric shock and energy hazards (Cl.2.1)				
EL 2104	Electrical safety	SELV Circuits (Cl.2.2)				
EL 2105	Electrical safety	TNV Circuits (Cl.2.3)				
EL 2106	Electrical safety	Limited current circuits (Cl.2.4)				
EL 2107	Electrical safety	Limited Power sources (Cl.2.5)				
EL 2108	Electrical safety	Provisions for earthing and bonding (Cl.2.6)				
EL 2109	Electrical safety	Overcurrent and earth fault protection in primary circuits (Cl.2.7)				
EL 2110	Electrical safety	Safety Interlocks (Cl.2.8)				
EL 2111	Electrical safety	Electrical Insulation (Cl.2.9)				
EL 2112	Electrical safety	Clearances, Creepage distances and distances through insulation (Cl.2.10)				
EL 2113	Wiring	Wiring, connections and supply (Cl.3)				
EL 2114	Wiring	Connection to a main supply (Cl.3.2)				
EL 2115	Wiring	Wiring terminals for connection of external conductors (Cl.3.3)				
EL 2116	Wiring	Disconnection for the main supply (Cl.3.4)				
EL 2117	Wiring	Interconnection of equipment (CI.3.5)				
EL 2118	Mechanical properties	Stability (Cl.4.1)				
EL 2119	Mechanical properties	Mechanical strength (Cl.4.2)				

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 4 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

EL 2120	Mechanical properties	Design and construction (CI.4.3)			
EL 2121	Mechanical properties	Protection against hazardous moving parts (Cl.4.4)			
EL 2122	Thermal Properties	Thermal requirements (Cl.4.5)			
EL 2123	Mechanical properties	Openings in Enclosures (Cl.4.6)			
EL 2124	Fire Safety	Resistance to fire (Cl.4.7)			
EL 2125	Insulating properties	Electrical requirements and simulated abnormal conditions(Cl.5),5.1			
EL 2126	Insulating properties	Electric Strength (CI.5.2)			
EL 2127	Insulating properties	Abnormal operating and fault conditions (Cl.5.3)			
EL 2128	Communicating connection	Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment(CI.6.1)			
EL 2129	Communicating connection	Protection of equipment users from overvoltages on telecommunication networks (Cl.6.2)			
EL 2130	Communicating connection	Protection of the telecommunication wiring system from overheating (Cl.6.3)			
EL 2131	Connection to cable distribution systems	Connection to cable distribution systems (CI.7)			
EL 2132	Fire safety	Tests for resistance to heat and fire (Annex A)			
EL 2133	Insulating properties	Motor tests under abnormal conditions (Annex B)	_		
EL 2134	Electrical Safety	Transformers (Annex C)			
EL 2135	Insulating properties	Measuring Instruments For Touch-Current Tests (Annex D)			
EL 2136	Thermal Properties	Temperature Rise Of A Winding(Annex E)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 5 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

EL 2137	Electrical safety	Measurement Of Clearances And		
		Creepage Distances(Annex F)		
EL 2138	Electrical safety	Alternative Method For Determining Minimum Clearances(Annex G)		
EL 2139	Radiation Safety	lonizing Radiation(Annex H)		
EL 2140	Electrical Safety	Table of electrochemical potentials (Annex J)		
EL 2141	General Requirements	Thermal controls (Annex K)		
EL 2142	General Requirements	Normal load conditions for some types of electrical business equipment (Annex L)		
EL 2143	Electrical Safety	Criteria for telephone ringing signals (Annex M)		
EL 2144	Electrical safety	Impulse Test Generators(Annex N)		
EL 2145	General Requirements	Normative References(Annex P)		
EL 2146	General Requirements	Voltage dependent resistors (VDRs) (Annex Q)		
EL 2147	General Requirements	Examples Of Requirements For Quality Control Programmes(Annex R)		
EL 2148	General Requirements	Procedure For Impulse Testing (Annex S)		
EL 2149	Protection against Ingress of water	Guidance On Protection Against Ingress Of Water (Annex T)		
EL 2150	Wiring	Insulated Winding Wires For Use Without Interleaved Insulation (Annex U)		
EL 2151	Electrical Safety	Ac Power Distribution Systems(Annex V)		
EL 2152	Electrical Safety	Summation Of Touch Currents (Annex W)		
EL 2153	Electrical Safety	Maximum Heating Effect In Transformer Tests(Annex X)		

[LAB LOGO]

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 6 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

EL 2154	Radiation safety	Ultraviolet light conditioning test (Annex Y)		
EL 2155	Electrical Safety	Overvoltage Categories (Annex Z)		
EL 2156	Mechanical properties	Mandrel Test(Annex AA)		
EL 2157	Electrical Safety	Changes In The Second Edition(Annex BB)		
EL 2158	Electrical Safety	Evaluation Of Integrated Circuit (IC) Current Limiters (Annex CC)		
EL 2159	Mechanical properties	Requirements For The Mounting Means Of Rack-Mounted Equipment (Annex DD)		
EL 2160	Electrical Safety	Household And Home/Office Document/Media Shredders (Annex EE)		

Certificate: It is certified that the above tests were performed and found to be passi requirement tested.	ing/Failing in the
·	
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 7 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Copy of marking plate:	
Copy of marking label:	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 8 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Table – List of Attachments			
Attachment No.	Attachment Description		No. of pages in Attachment
Attachment – 1	Photo Document		xx
General remark	(S:		
	esented in this report relate only to the to be reproduced, except in full, without the reproduced in full, without the reproduced in full, without the reproduced in the repr	•	al of the Issuing testing
Possible test case	verdicts:		
- test case does not	apply to the test object:	N/A	
- test object does m	eet the requirement: F	P (Pass)	
- test object does no	ot meet the requirement: F	F (Fail)	
Testing	· · · · · · · · · · · · · · · · · · ·		
Date of receipt of te	st item:		
Date(s) of performa	nce of tests:		
Laboratory conditi	ons:		
Ambient Temperatu	re:		
Ambient Humidity	·		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 9 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Test item particulars	
Equipment mobility:	☐ movable ☐ hand-held ☐ transportable ☐ stationary ☐ for building-in ☐ direct plug-in
Connection to the mains:	 □ pluggable equipment [] type A [] type B □ permanent connection □ detachable power supply cord □ non-detachable power supply cord □ not directly connected to the mains
Operating condition:	☐ continuous ☐ rated operating / resting time:
Access location:	operator accessible restricted access location
Over voltage category (OVC):	OVC I OVC II OVC III OVC IV other:
Mains supply tolerance (%) or absolute mains supply	40%
values:	-10%, +6% <or> ±10%</or>
Class of equipment:	☐ Class I ☐ Class II ☐ Class III ☐ Not classified
Considered current rating of protective device as a	404 (5 1 1)
part of the building installation (A)	16A (for India)
Pollution degree (PD):	□ PD 1 □ PD 2 □ PD 3
IP protection class	IPXX or Not rated, indoor use only
Altitude during operation (m):	Up to 2000
Altitude of test laboratory (m):	< 1000
Mass of equipment (kg):	
Abbreviations that may be used throughout this te	st report:
PE/PB: protective earth/protective bonding	Pri primary
CB: circuit breaker	sec secondary
(SW)PS: (switching) power supply	gnd: ground
HV: high voltage	I/O input/output
PCB: printed circuit (wiring) board	ii: installation instruction
TIW: triple insulated wire	PSU: Power Supply Unit
B/I: built-in application (compliance shall	be guarantee in host equipment)
F/B/S/R Functional/Basic/Supplementary/Reinforced I	nsulation

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 10 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

General pro	duct	inforr	nation:
-------------	------	--------	---------

1) Application details / Description of the product:

Max. specified ambient temperature (°C).....: ?? °C

Laser classification < delete this line, if not applicable >

2) Differences between the models:

(N/A, one single model)

<0R>

< describe the constructional differences in such general terms, that the informed reader can still make a rough evaluation of their safety relevance >

Model No. tested with-in the family series .: ??

3) Options:

The equipment was tested without any optional accessory installed. Hence, this report does not cover parameters that are influenced by the installation of optional accessory that might affect safety in the meaning of this standard.

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 11 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to General Requirements

EL 2100 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
1.5	Components*	EL 2100-00		
1.5.1	General:	EL 2100-01		
	Components shall be complying with IEC 60950-1 or relevant component standard.			
	Components and subassemblies approved for IEC 62368-1 can be considered as complying with this standard			
1.5.2	Evaluation and testing of components	EL 2100-02		
1.5.3	Thermal controls	EL 2100-03		
1.5.4	Transformers	EL 2100-04		
1.5.5	Interconnecting cables*	EL 2100-05		
1.5.6	Capacitors bridging insulation *	EL 2100-06		
1.5.7	Resistors bridging insulation	EL 2100-07		
1.5.7.1	Resistors bridging functional, basic or supplementary insulation*	EL 2100-08		
1.5.7.2	Resistors bridging double or reinforced insulation between a.c. mains and other circuits	EL 2100-09		
1.5.7.3	Resistors bridging double insulation or reinforced insulation between the a.c. mains supply and circuits connected to an antenna or coaxial cable	EL 2100-10		
1.5.8	Components in equipment for IT power distribution systems*	EL 2100-11		
1.5.9	Surge suppressors	EL 2100-12		
1.5.9.1	General*	EL 2100-13		
1.5.9.2	Protection of VDRs*	EL 2100-14		
1.5.9.3	Bridging of functional insulation by a VDR*	EL 2100-15		
1.5.9.4	Bridging of basic insulation by a VDR*	EL 2100-16		
1.5.9.5	Bridging of supplementary, double or reinforced insulation by a VDR*	EL 2100-17		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 12 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 13 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2101 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
1.6	Power interface*	EL 2101-00		
1.6.1	AC power distribution systems*	EL 2101-01		
1.6.2	Input current	EL 2101-02		
1.6.3	Voltage limit of hand-held equipment*	EL 2101-03		
1.6.4	Neutral conductor *	EL 2101-04		

*- Total number of Requirements to be	observed / inspected =
Total No of applicable Requirement	=
No of Requirements for which the sa	mple passed=
Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample passe	ed=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/ failing in the
(Approving Authority)	

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 14 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Marking Requirements

EL 2102 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
1.7	Marking and instructions*	EL 2102-00	restresult/observation	verdict
		EL 2102-00		
1.7.1	Power rating and identification markings			
1.7.1.1	Power rating marking*	EL 2102-01		
	Rated voltage(s) or voltage ranges(s) (V)*.	EL 2102-02		
	Multiple mains supply connections*.	EL 2102-03		
	Symbol for nature of supply, for d.c. only*:	EL 2102-04		
	Rated frequency or rated frequency range (Hz) *:	EL 2102-05		
	Rated current (mA or A)*:	EL 2102-06		
1.7.1.2	Identification markings*	EL 2102-07		
	Manufacturer's name or trade- mark or identification mark *:	EL 2102-08		
	Model identification or type reference *:	EL 2102-09		
	Symbol for Class II equipment only*:	EL 2102-10		
	Other markings and symbols*:	EL 2102-11		
1.7.1.3	Use of graphical symbols*	EL 2102-12		
1.7.2	Safety instructions and marking*	EL 2102-13		
1.7.2.1	General	EL 2102-14		
1.7.2.2	Disconnect devices*	EL 2102-15		
1.7.2.3	Overcurrent protective devices*	EL 2102-16		
1.7.2.4	IT power distribution systems*	EL 2102-17		
1.7.2.5	Operator access with a tool*	EL 2102-18		
1.7.2.6	Ozone*	EL 2102-19		
1.7.3	Short duty cycles*	EL 2102-20		
1.7.4	Supply voltage adjustment*	EL 2102-21		
1.7.5	Power outlets on the equipment*	EL 2102-22		
1.7.6	Fuse identification (marking, special fusing characteristics, cross-reference)	EL 2102-23		
	Fuse(s) shall clearly and adequately marked with fuse number and rating*.			
1.7.7	Wiring terminals	EL 2102-24		

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 15 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Marking Requirements

EL 2102 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
1.7.7.1	Protective earthing and bonding terminals*	EL 2102-25		
1.7.7.2	Terminals for a.c. mains supply conductors*	EL 2102-26		
1.7.7.3	Terminals for d.c. mains supply conductors*	EL 2102-27		
1.7.8	Controls and indicators	EL 2102-28		
1.7.8.1	Identification, location and marking *:	EL 2102-29		
1.7.8.2	Colours*	EL 2102-30		
1.7.8.3	Symbols according to IEC 60417*:	EL 2102-31		
1.7.8.4	Markings using figures* :	EL 2102-32		
1.7.9	Isolation of multiple power sources*	EL 2102-33		
1.7.10	Thermostats and other regulating devices*	EL 2102-34		
1.7.11	Durability	EL 2102-35		
1.7.12	Removable parts*	EL 2102-36		
1.7.13	Replaceable batteries*	EL 2102-37		
	Language(s)			
1.7.14	Equipment for restricted access locations*	EL 2102-38		

*- Total ทเ	ımber of Requirements to be obsei	ved / inspecte	d =	
Total N	o of applicable Requirement		=	
No of R	equirements for which the sample	passed=		
Total num	ber of tests to be conducted =			
Total No o	of applicable Tests =			
No. of tes	ts for which the sample passed=			
		were performe	ed and found to be passing/failing in the	
requireme	ent tested.			
(Approvin	g Authority)			

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 16 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Electrical Safety

TRF No. BIS_IT/PR_IS13252_V1.2

EL 2103 - V1.4

Verdict

	locations					
*- Total	*- Total number of Requirements to be observed / inspected =					
Total	No of applicable Requirement		=			
No of	Requirements for which the san	nple pas	sed=			
Total nu	imber of tests to be conducted	=				
Total No	o of applicable Tests	=				
No. of te	ests for which the sample passed	d=				
Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.						
(Approv	ing Authority)					

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 17 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2104 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
2.2	SELV circuits*	EL 2104-00		
2.2.2	Voltages under normal conditions	EL 2104-01		
2.2.3	Voltages under fault conditions	EL 2104-02		
2.2.4	Connection of SELV circuits to other circuits*:	EL 2104-03		

*- Total number of Requirements to be obs	erved / inspecte	d =
·	erved / mspecie	
Total No of applicable Requirement		=
No of Requirements for which the samp	le passed=	
Total number of tests to be conducted =		
Total No of applicable Tests =		
No. of tests for which the sample passed=		
Certificate: It is certified that the above tes requirement tested.	s were performe	ed and found to be passing/failing in the
(Approving Authority)		

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 18 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Electrical Safety

EL 2105 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
2.3	TNV circuits*	EL 2105-00		
2.3.1	Type of TNV circuits: TNV-1 / TNV-2 / TNV-3	EL 2105-01		
	a) Limits of TNV-1:	EL 2105-02		
	b) Limits of TNV-2 or TNV-3: Continuous voltages, combination of AC and DC values, are such that : $\frac{U_{\rm ac}}{71} + \frac{U_{\rm dc}}{120} \le 1$	EL 2105-03		
2.3.2	Separation from other circuits and from accessible parts*	EL 2105-04		
2.3.2.1	General Requirements	EL 2105-05		
2.3.2.2	Protection by basic insulation	EL 2105-06		
2.3.2.3	Protection by earthing	EL 2105-07		
2.3.2.4	Protection by other constructions :	EL 2105-08		
2.3.3	Separation from hazardous voltages	EL 2105-09		
2.3.4	Connection of TNV circuits to other circuits	EL 2105-10		
2.3.5	Test for operating voltages generated externally	EL 2105-11		

	generated externally		
*- Total nu	ımber of Requirements to be ol	served / inspecte	d = d
Total N	o of applicable Requirement		=
No of R	equirements for which the sam	ole passed=	
T-4-1	h - n - f	_	
	ber of tests to be conducted	=	
Total No o	of applicable Tests =		
No. of tes	ts for which the sample passed	=	
Certificate requireme		sts were performe	ed and found to be passing/failing in the
(Approvin	g Authority)		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 19 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2106 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
2.4	Limited current circuits *	EL 2106-00		
2.4.1	General requirements *	EL 2106-01		
2.4.2	Limit values	EL 2106-02		
2.4.3	Connection of limited current circuits to other circuits*	EL 2106-03		

*- Total ทเ	umber of Requirements to be	observ	ved / inspected	d =		
Total N	o of applicable Requirement			=		
No of R	Requirements for which the sai	mple p	passed=			
Total num	ber of tests to be conducted	=				
Total No o	of applicable Tests	=				
No. of tes	ts for which the sample passe	ed=				
Certificate requireme	e: It is certified that the above tent tested.	tests v	were performe	d and found to l	be passing/failing i	n the
(Approvin	g Authority)					

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 20 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2107 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
2.5	Limited power sources *	EL 2107-00		
	a) Inherently limited output	EL 2107-01		
	b) Impedance limited output	EL 2107-02		
	c) Regulating network limited output under normal operating and single fault condition Use of integrated circuit (IC) current limiters	EL 2107-03	(See Annex CC)	
	d) Overcurrent protective device limited output	EL 2107-04		
	Max. output voltage (V), Max. output current (A), Max. apparent power (VA)	EL 2107-05		
	Current rating of overcurrent protective device (A)	EL 2107-06		

	Max. output current (A),			
	Max. apparent power (VA)			
	Current rating of overcurrent protective device (A)	EL 2107-06		
*- Total nu	ımber of Requirements to be obser	ved / inspected	d = 01	
	o of applicable Requirement	ved / mapeoted	=	
	equirements for which the sample	passed=		
Total num	ber of tests to be conducted = 06	3		
Total No c	of applicable Tests =			
No. of test	s for which the sample passed=			
Certificate requireme		were performe	d and found to be passing/failing in the	
(Approving	g Authority)			

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 21 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Electrical Safety

EL 2108 - V1.4

01	T //D :			
Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
2.6	Provisions for earthing and bonding*	EL 2108-00		
2.6.1	Protective earthing	EL 2108-01		
2.6.2	Functional earthing: The Functional earthing either separated from hazardous voltages by double or reinforced insulation or by protectively earthed screen or conductive part separated by at least basic insulation, or safely connected to Protective Bonding Conductor.*	EL 2108-02		
	Use of symbol for functional earthing:*	EL 2108-03		
2.6.3	Protective earthing and protective bonding conductors*	EL 2108-04		
2.6.3.2	Size of protective earthing conductors	EL 2108-05		
	Rated current (A), cross-sectional area (mm2),			
2.6.3.3	Size of protective bonding conductors	EL 2108-06		
	Protective current Rating (A), cross-sectional area (mm2)			
2.6.3.4	Resistance of earthing conductors and their terminations; resistance (Ω) , voltage drop (V), test current (A), duration (min):	EL 2108-07		
2.6.3.5	Colour of insulation*:	EL 2108-08		
2.6.4	Terminals			
2.6.4.2	Protective earthing and bonding terminals : Rated current(A), Type, Nominal thread diameter (mm)	EL 2108-09		
2.6.4.3	Separation of the protective earthing conductor from protective bonding conductors*	EL 2108-10		
2.6.5	Integrity of protective earthing*			
2.6.5.1	Interconnection of equipment*	EL 2108-11		
2.6.5.2	Components in protective earthing conductors and protective bonding conductors*	EL 2108-12		
2.6.5.3	Disconnection of protective earth*	EL 2108-13		
2.6.5.4	Parts that can be removed by an operator*	EL 2108-14		
2.6.5.5	Parts removed during servicing*	EL 2108-15		

[LAB LOGO]

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 22 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

2.6.5.6	Corrosion resistance*	EL 2108-16	
2.6.5.7	Screws for protective bonding*	EL 2108-17	
2.6.5.8	Reliance on telecommunication network or cable distribution system*	EL 2108-18	

	ı.	3			
2.6.5.8	Reliance on telecom network or cable dis		EL 2108-18		
Total N	ımber of Requiremer o of applicable Requ	irement	- =		
No of R	equirements for which	ch the sample pas	ssed=		
Total num	ber of tests to be cor	nducted =			
Total No c	of applicable Tests	=			
No. of test	s for which the samp	ole passed=			
Certificate requireme		e above tests wer	re performed a	nd found to be passing/failing in the	
(Approvin	g Authority)				

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 23 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Electrical Safety

EL 2109 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
2.7	Overcurrent and earth fault protection in primary circuits*	EL 2109-00		
2.7.1	Basic requirements: Protection in primary circuits against overcurrents, short- circuits and earth faults shall be provided, either as an integral part of the equipment or as part of building installation.	EL 2109-01		
	If pluggable equipment Type B or permanently connected equipment relies on protective device external to the equipment for protection, the equipment installation Instructions shall so state and shall also specify the requirements for short-circuit protection or overcurrent protection or, where necessary, for both.			
2.7.2	Faults not simulated in 5.3.7* need not be fitted as an integral part of the equipment	EL 2109-02		
2.7.3	Short-circuit backup protection	EL 2109-03		
2.7.4	Number and location of protective devices :	EL 2109-04		
2.7.5	Protection by several devices*	EL 2109-05		
2.7.6	Warning to service personnel*:	EL 2109-06		

L			_		
*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sal	•	= =			
Total number of tests to be conducted Total No of applicable Tests No. of tests for which the sample passe	= = d=				
Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.					
(Approving Authority)					

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 24 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Electrical Safety

EL 2110 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
2.8	Safety Interlocks*	EL 2110-00		
2.8.1	General principles*	EL 2110-01		
2.8.2	Protection requirements	EL 2110-02		
2.8.3	Inadvertent reactivation	EL 2110-03		
2.8.4	Fail-safe operation	EL 2110-04		
2.8.5	Moving parts	EL 2110-05		
2.8.6	Overriding*	EL 2110-06		
2.8.7	Switches, relays and their related circuits	EL 2110-07		
2.8.7.1	Separation distances for contact gaps and their related circuits`	EL 2110-08		
2.8.7.2	Overload test	EL 2110-09		
2.8.7.3	Endurance test	EL 2110-10		
2.8.7.4	Electric strength test	EL 2110-11		
2.8.8	Mechanical actuators	EL 2110-12		

2.8.8	Mechanical actuators	EL 2110-12		
	•	•		
*- Total ทเ	umber of Requirements to be ob-	served / inspecte	d =	
Total N	o of applicable Requirement		=	
No of R	equirements for which the samp	le passed=		
Total num	ber of tests to be conducted =			
Total No o	of applicable Tests =			
No. of tes	ts for which the sample passed=			
	e: It is certified that the above tesent tested.	ts were performe	ed and found to be passing/failing in the	
(Approvin	g Authority)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 25 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2111 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
2.9	Electrical insulation*	EL 2111-00		
2.9.1	Properties of insulating materials*	EL 2111-01		
2.9.2	Humidity conditioning	EL 2111-02		
	Relative Humidity: 93 ±3 %, Temperature: t at 40 ± 2°C Duration: 120 hours			
2.9.3	Grade of insulation*	EL 2111-03		
2.9.4	Separation from hazardous voltages*	EL 2111-04		
	Method(s) used			

Method(s) used			
*- Total number of Requirements to be obser	ved / inspected	:d =	
Total No of applicable Requirement		=	
No of Requirements for which the sample	passed=		
Total number of tests to be conducted =			
Total No of applicable Tests =			
No. of tests for which the sample passed=			
Certificate: It is certified that the above tests requirement tested.	were performe	ed and found to be passing/failing in the	
(Approving Authority)			

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 26 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Electrical Safety

EL 2112 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
2.10	Clearances, creepage distances and distances through Insulation*	EL 2112-00		
2.10.1.1	Frequency *	EL 2112-01		
2.10.1.2	Pollution degrees*	EL 2112-02		
2.10.1.3	Reduced values for functional insulation	EL 2112-03		
2.10.1.4	Intervening unconnected conductive parts	EL 2112-04		
2.10.1.5	Insulation with varying dimensions	EL 2112-05		
2.10.1.6	Special separation requirements	EL 2112-06		
2.10.1.7	Insulation in circuits generating starting pulses	EL 2112-07		
2.10.2	Determination of working voltage	EL 2112-08		
2.10.2.2	RMS working voltage	EL 2112-09		
2.10.2.3	Peak working voltage	EL 2112-10		
2.10.3	Clearances	EL 2112-11		
2.10.3.1	General	EL 2112-12		
2.10.3.2	Mains transient voltages*			
	a) AC mains supply * :	EL 2112-13		
	b) Earthed d.c. mains supplies*	EL 2112-14		
	c) Unearthed d.c. mains supplies* :	EL 2112-15		
	d) Battery operation* :	EL 2112-16		
2.10.3.3	Clearances in primary circuits	EL 2112-17		
2.10.3.4	Clearances in secondary circuits	EL 2112-18		
2.10.3.5	Clearances in circuits having starting pulses	EL 2112-19		
2.10.3.6	Transients from a.c. mains supply :	EL 2112-20		
2.10.3.7	Transients from d.c. mains supply :	EL 2112-21		
2.10.3.8	Transients from telecommunication networks and cable distribution systems	EL 2112-22		
2.10.3.9	Measurement of transient voltages			
	a) Transients from a mains supply	EL 2112-23		
	For an a.c. mains supply			
	For a d.c. mains supply			
	b) Transients from a telecommunication network	EL 2112-24		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 27 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

		1	I	
2.10.4	Creepage distances*	EL 2112-25		
2.10.4.1	General	EL 2112-26		
2.10.4.2	Material group and comparative tracking index : CTI tests*	EL 2112-27		
2.10.4.3	Minimum creepage distances	EL 2112-28		
2.10.5	Solid insulation	EL 2112-29		
2.10.5.1	General	EL 2112-30		
2.10.5.2	Distances through insulation	EL 2112-31		
2.10.5.3	Insulating compound as solid insulation	EL 2112-32		
2.10.5.4	Semiconductor devices	EL 2112-33		
2.10.5.5.	Cemented joints	EL 2112-34		
2.10.5.6	Thin sheet material – General	EL 2112-35		
2.10.5.7	Separable thin sheet material	EL 2112-36		
2.10.5.8	Non-separable thin sheet material	EL 2112-37		
2.10.5.9	Thin sheet material – standard test procedure	EL 2112-38		
	Electric strength test as per Cl.5.2.2			
2.10.5.10	Thin sheet material – alternative test procedure	EL 2112-39		
	Electric strength test as per Cl.5.2.2			
2.10.5.11	Insulation in wound components	EL 2112-40		
2.10.5.12	Wire in wound components			
	If Peak Working voltage >71 V			
	a) Basic insulation not under stress	EL 2112-41		
	b) Basic, supplementary, reinforced insulation	EL 2112-42		
	c) Compliance with Annex U	EL 2112-43		
	d) Where two winding wires in contact inside wound component; angle between 45° and 90°	EL 2112-44		
2.10.5.13	Wire with solvent-based enamel in wound components			
	a) Electric strength test (Type test as per Cl.5.2.2)	EL 2112-45		
	b) Electric Strength test (Routine test as per Cl.5.2.2)	EL 2112-46		
2.10.5.14	Additional insulation in wound components			
	If Peak Working Voltage >71V			
	a) Basic insulation not under stress	EL 2112-47		
	•	•		

[LAB LOGO]

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 28 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

	b) Supplementary, reinforced insulation	EL 2112-48	
2.10.6	Construction of printed boards*		
2.10.6.1	Uncoated printed boards	EL 2112-49	
2.10.6.2	Coated printed boards	EL 2112-50	
2.10.6.3	Insulation between conductors on the same inner surface of a printed board	EL 2112-51	
2.10.6.4	Insulation between conductors on different surfaces of a printed board*		
	a) Minimum Thickness of insulation: 0.4mm or	EL 2112-52	
	b) Confirm with one of the specification and pass the relevant tests as per Table 2R	EL 2112-53	
2.10.7	Component external terminations	EL 2112-54	
2.10.8	Tests on coated printed boards and coated components		
2.10.8.1	Sample preparation and preliminary inspection*	EL 2112-55	
2.10.8.2	Thermal conditioning	EL 2112-56	
2.10.8.3	Electric strength test	EL 2112-57	
2.10.8.4	Abrasion resistance test	EL 2112-58	
2.10.9	Thermal cycling	EL 2112-59	
2.10.10	Test for Pollution Degree 1 environment and insulating compound	EL 2112-60	
2.10.11	Tests for semiconductor devices and cemented joints	EL 2112-61	
2.10.12	Enclosed and sealed parts	EL 2112-62	

*- Total number of Requirements to be observed / inspected =
Total No of applicable Requirement =
No of Requirements for which the sample passed=

Total number of tests to be conducted :

Total No of applicable Tests =

No. of tests for which the sample passed=

Certificate: It is certified that the above tests were performed and found to be passing/failing in t	he
equirement tested.	

	• • • • • • • • • • • • • • • • • • • •	
(Approving	Authority)	

(Approving Authority)

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 29 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Wiring

EL 2113 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
3.0	Wiring, connections and supply*	EL 2113-00		
3.1.1	Current rating and overcurrent protection	EL 2113-01		
3.1.2	Protection against mechanical damage*	EL 2113-02		
3.1.3	Securing of internal wiring*	EL 2113-03		
3.1.4	Insulation of conductors	EL 2113-04		
3.1.5	Beads and ceramic insulators	EL 2113-05		
3.1.6	Screws for electrical contact pressure*	EL 2113-06		
3.1.7	Insulating materials in electrical connections*	EL 2113-07		
3.1.8	Self-tapping and spaced thread screws*	EL 2113-08		
3.1.9	Termination of conductors : 10 N pull test	EL 2113-09		
3.1.10	Sleeving on wiring*	EL 2113-10		

*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sa	· =
Total number of tests to be conducted Total No of applicable Tests	=
No. of tests for which the sample passe	ed=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 30 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Wiring

EL 2114 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
3.2	Connection to a mains supply*	EL 2114-00		
3.2.1	Means of connection			
3.2.1.1	Connection to an a.c. mains supply*	EL 2114-01		
3.2.1.2	Connection to a d.c. mains supply*	EL 2114-02		
3.2.2	Multiple supply connections	EL 2114-03		
3.2.3	Permanently connected equipment	EL 2114-04		
3.2.4	Appliance inlets: Are so Located that parts at hazardous voltage are not accessible during insertion or removal of the connector, connector can be inserted without difficulty and after insertion of the connector, the equipment is not supported by the connector for any position of normal use on a flat surface (appliance inlets complying with IEC 60309 or IEC 60320 considered to comply with this requirement.	EL 2114-05		
3.2.5	Power supply cords			
3.2.5.1	AC power supply cords*	EL 2114-06		
	Rated current (A), cross-sectional area (mm²), AWG			
3.2.5.2	DC power supply cords*	EL 2114-07		
3.2.6	Cord anchorages and strain relief			
	Mass of the equipment: Pull Force (N):	EL 2114-08		
	b) Longitudinal displacement: 2 mm (Max)	EL 2114-09		
3.2.7	Protection against mechanical damage	EL 2114-10		
3.2.8	Cord guards			
	a) Diameter or minor dimension D (mm) : Test mass (g) :	EL 2114-11		
	b) Radius of curvature of cord : 1.5 D (Min)	EL 2114-12		
3.2.9	Supply wiring space	EL 2114-13		

^{*-} Total number of Requirements to be observed / inspected =
Total No of applicable Requirement =
No of Requirements for which the sample passed=
Total number of tests to be conducted =
Total No of applicable Tests =
No. of tests for which the sample passed=
Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.

(Approving Authority)

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 31 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Wiring

EL 2115 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
3.3	Wiring terminals for connection of external conductors*	EL 2115-00		
3.3.1	Wiring terminals*	EL 2115-01		
3.3.2	Connection of non-detachable power supply cords	EL 2115-02		
3.3.3	Screw terminals*	EL 2115-03		
3.3.4	Conductor sizes to be connected	EL 2115-04		
	Rated current (A), cord/cable type, cross-sectional area (mm2)			
3.3.5	Wiring terminal sizes	EL 2115-05		
	Rated current (A), type, nominal thread diameter (mm)			
3.3.6	Wiring terminal design	EL 2115-06		
3.3.7	Grouping of wiring terminals*	EL 2115-07		
3.3.8	Stranded wire	EL 2115-08		

*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sa	· =
Total number of tests to be conducted Total No of applicable Tests No. of tests for which the sample passe	= = ed=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 32 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Wiring

EL 2116 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
3.4	Disconnection from the mains supply*	EL 2116-00		
3.4.1	General Requirement A disconnect device or devices shall be provided to disconnect the equipment from the mains supply for servicing.	EL 2116-01		
3.4.2	Disconnect devices*	EL 2116-02		
3.4.3	Permanently connected equipment*	EL 2116-03		
3.4.4	Parts which remain energized*	EL 2116-04		
3.4.5	Switches in flexible cords*	EL 2116-05		
3.4.6	Number of poles - single-phase and d.c. equipment*	EL 2116-06		
3.4.7	Number of poles - three-phase equipment*	EL 2116-07		
3.4.8	Switches as disconnect devices*	EL 2116-08		
3.4.9	Plugs as disconnect devices*	EL 2116-09		
3.4.10	Interconnected equipment*	EL 2116-10		
3.4.11	Multiple power sources*	EL 2116-11		

*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sa	· =
Total number of tests to be conducted Total No of applicable Tests No. of tests for which the sample passe	= = ed=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 33 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Wiring

EL 2117 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
3.5	Interconnection of equipment*	EL 2117-00		
3.5.1	General requirements*	EL 2117-01		
3.5.2	Types of interconnection circuits*	EL 2117-02		
3.5.3	ELV circuits as interconnection circuits *	EL 2117-03		
3.5.4	Data ports for additional equipment	EL 2117-04		

	equipment			
Total No	nber of Requirements to be of applicable Requirement quirements for which the sai		·	d = =
Total No of	er of tests to be conducted applicable Tests for which the sample passe	= = ed=		
Certificate: requiremen		tests	were performe	ed and found to be passing/failing in the
(Approving	Authority)			

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 34 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Mechanical Properties

EL 2118 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
4	PHYSICAL REQUIREMENTS*	EL 2118-00		
4.1	Stability	EL 2118-01		
	a) A unit having a mass of 7 kg or more shall not fall over when tilted to an angle of 10° from its normal upright position. Alternatively, the unit is placed in its intended position of use on a plane, inclined at an angle of 10° to the horizontal, and then rotated slowly through an angle of 360° about its normal vertical axis.			
	b) A floor-standing unit having a mass of 25 kg or more shall not fall over when a force equal to 20 % of the weight of the unit, but not more than 250 N, is applied in any direction except upwards, at a height not exceeding 2 m from the floor.	EL 2118-03		
	c) A floor-standing unit shall not fall over when a constant downward force of 800 N is applied at the point of maximum moment to any horizontal surface of at least 125 mm by at least 200 mm, at a height up to 1 m from the floor.	EL 2118-04		

*- Total nur	mber of Requirements to be	obsei	rved / inspected	i =	
Total No	of applicable Requirement			=	
No of Re	equirements for which the sar	nple	passed=		
Total numb	er of tests to be conducted	=			
Total No of	applicable Tests	=			
No. of tests	for which the sample passe	d=			
Certificate: requiremer		ests	were performe	d and found to be passing/failing in	the
(Approving	Authority)				

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 35 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Mechanical Properties

EL 2119 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
4.2	Mechanical Strength	EL 2119-00		
4.2.1	General	EL 2119-01		
4.2.2	Steady force test, 10 N	EL 2119-02		
4.2.3	Steady force test, 30 N	EL 2119-03		
4.2.4	Steady force test, 250 N	EL 2119-04		
4.2.5	Impact test	EL 2119-05		
	a) Fall test as per Fig. 4A	EL 2119-06		
	b) Swing test as per Fig. 4A	EL 2119-07		
4.2.6	Drop test; height (mm) :	EL 2119-08		
4.2.7	Stress relief test	EL 2119-09		
4.2.8	Cathode Ray Tubes	EL 2119-10		
4.2.9	High Pressure Lamps*	EL 2119-11		
4.2.10	Wall or ceiling mounted equipment; force(N)	EL 2119-12		

*- Total number of Requirements to be	observed / inspected =				
Total No of applicable Requirement	=				
No of Requirements for which the sa	mple passed=				
Total number of tests to be conducted	=				
Total No of applicable Tests	=				
No. of tests for which the sample passe	d=				
Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.					
(Approving Authority)					

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 36 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Mechanical Properties

EL 2120 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
4.3	Design and Construction*	EL 2120-00		
4.3.1	Edges and corners*	EL 2120-01		
4.3.2	Handles and manual controls; force (N)	EL 2120-02		
4.3.3	Adjustable controls	EL 2120-03		
4.3.4	Securing of parts	EL 2120-04		
4.3.5	Connections by Plugs and Sockets*	EL 2120-05		
4.3.6	Direct plug-in equipment	EL 2120-06		
	Torque	EL 2120-07		
	Compliance with the relevant mains plug standard	EL 2120-08		
4.3.7	Heating elements in earthed equipment*	EL 2120-09		
4.3.8	Batteries Portable secondary sealed cells and batteries (other than button) containing alkaline or other non-acid electrolyte shall comply with IEC 62133			
	a) Overcharging of a rechargeable battery	EL 2120-10		
	b) Unintentional charging of a non-rechargeable battery	EL 2120-11		
	c) Reverse charging of a rechargeable battery	EL 2120-12		
	d) Excessive discharging rate for any battery	EL 2120-13		
	e) Electric strength as per Cl.5.3.9.2	EL 2120-14		
4.3.9	Oil & grease*	EL 2120-15		
4.3.10	Dust, powders, liquids and gases	EL 2120-16		
4.3.11	Containers for liquids or gases	EL 2120-17		
4.3.12	Flammable liquids	EL 2120-18		
4.3.13	Radiation			
4.3.13.2	Ionizing radiation	EL 2120-19		
4.3.13.3	Effect of ultraviolet (UV) radiation on materials	EL 2120-20		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 37 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

4.3.13.4	Human exposure to ultraviolet (UV) radiation	EL 2120-21	
4.3.13.5	Lasers (including laser diodes) and LED's:		
4.3.13.5.1	Lasers (including laser diodes) For laser see IEC 60825-1, respective part as applicable.	EL 2120-22	
	Laser class		
4.3.13.5.2	Light emitting diodes (LED's)	EL 2120-23	
4.3.13.6	Other types*	EL 2120-24	

	9 ()			Ĺ
4.3.13.6	Other types*	EL 2120-24		
*- Total numl	per of Requirements to be obse	rved / inspecte	ed =	
Total No o	f applicable Requirement		=	
No of Req	uirements for which the sample	passed=		
Total numbe	r of tests to be conducted =			
Total No of a	pplicable Tests =			
No. of tests f	or which the sample passed=			
Certificate: It requirement		were perform	ed and found to be passing/failing in the	
(Approving A	authority)			

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 38 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Mechanical Properties

EL 2121 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
4.4	Protection against hazardous moving parts	EL 2121-00		
4.4.1	General	EL 2121-01		
4.4.2	Protection in operator access areas	EL 2121-02		
4.4.3	Protection in restricted access locations *	EL 2121-03		
4.4.4	Protection in service access areas*	EL 2121-04		
4.4.5	Protection against moving fan blades	EL 2121-05		
4.4.5.1	General*	EL 2121-06	m = r = N = K =	
	Not considered likely to cause pain or injury. a):	EL 2121-07	$\frac{r/\text{min}}{15000} + \frac{K \text{ factor}}{2400} =$	
	Is considered likely to cause pain, not injury. b)	EL 2121-08	$\frac{r/\min}{22000} + \frac{K \text{ factor}}{3 600} =$	
	Considered likely to cause injury. c)	EL 2121-09		
4.4.5.2	Protection for users*	EL 2121-10		
	Use of symbol or warning*	EL 2121-11		
4.4.5.3	Protection for service persons*	EL 2121-12		
	Use of symbol or warning *	EL 2121-13		

*- Total number of Requirements to be	observed / inspected	=			
Total No of applicable Requirement		=			
No of Requirements for which the sa	mple passed=				
Total number of tests to be conducted	=				
Total No of applicable Tests	=				
No. of tests for which the sample passe	ed=				
Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.					
(Approving Authority)					

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 39 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Thermal Properties

EL 2122 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
4.5	Thermal Requirements*	EL 2122-00		
4.5.1	General	EL 2122-01		
4.5.2	Temperature tests	EL 2122-02		
4.5.3	Temperature limits for materials*	EL 2122-03		
4.5.4	Touch temperature limits*	EL 2122-04		
4.5.5	Resistance to abnormal heat	EL 2122-05		

*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sai	· =
Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample passe	d=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 40 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Mechanical Properties

EL 2123 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
4.6	Openings in enclosures*	EL 2123-00		
4.6.1	Top and side openings	EL 2123-01		
	Dimensions (mm) :			
4.6.2	Bottoms of fire enclosures :	EL 2123-02		
	Construction of the bottom, dimensions (mm):			
4.6.3	Doors or covers in fire enclosures*	EL 2123-03		
4.6.4	Openings in transportable equipment	EL 2123-04		
4.6.4.1	Constructional design measures	EL 2123-05		
	Dimensions (mm)			
4.6.4.2	Evaluation measures for larger openings	EL 2123-06		
4.6.4.3	Use of metallized parts	EL 2123-07		
4.6.5	Adhesives for constructional purposes: Compliance is checked by examination of the construction and of the available data. If such data is not available, compliance is checked by the following tests.	EL 2123-08		
	a)Temperature Conditioning at : 100 °C \pm 2 °C for one week; or 90 °C \pm 2 °C for three weeks; or 82 °C \pm 2 °C for eight weeks.	EL 2123-09		
	After temperature conditioning b) Leave the sample between 20°C to 30°C for 1 hour	EL 2123-10		
	c) Place the sample at - 40°C±2°C for 4 hours	EL 2123-11		
	d) Remove and allow the sample to come to any convenient temperature between 20 °C and 30 °C for 8 h;	EL 2123-12		
	e) Place the sample in a cabinet at 91 % to 95 % relative humidity for 72 h;	EL 2123-13		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 41 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

f) Remove the sample and leave it at any convenient temperature between 20 °C and 30 °C for 1 h;	EL 2123-14	
g) Place the sample in an oven at the temperature used for the temperature conditioning for 4 h;	EL 2123-15	
h) Remove the sample and allow it to reach any convenient temperature between 20 °C; and 30 °C for 8 h.	EL 2123-16	
i) The sample is then immediately subjected to the tests of Cl.4.2 as applicable.	EL 2123-17	

	tests of Cl.4.2 as applicable.		
*- Total nur	nber of Requirements to be obser	ved / inspecte	d =
Total No	of applicable Requirement		=
No of Re	equirements for which the sample	passed=	
Total numb	er of tests to be conducted =		
Total No of	applicable Tests =		
No. of tests	for which the sample passed=		
		were performe	ed and found to be passing/failing in the
requiremen	t tested.		
(Approving	Authority)		

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 42 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Fire Safety

EL 2124 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
4.7	Resistance to fire*	EL 2124-00		
4.7.1	Reducing the risk of ignition and spread of flame			
	Method 1, selection and application of components wiring and materials OR	EL 2124-01		
	Method 2, application of all of simulated fault condition tests	EL 2124-02		
4.7.2	Conditions for a fire enclosure*			
4.7.2.1	Parts requiring a fire enclosure*	EL 2124-03		
4.7.2.2	Parts not requiring a fire enclosure	EL 2124-04		
4.7.3	Materials*	EL 2124-05		
4.7.3.1	General*	EL 2124-06		
	a)Class of material used*	EL 2124-07		
	b) Where HB40 CLASS MATERIAL, HB75 CLASS MATERIAL or HBF CLASS FOAMED MATERIAL, is required, material passing the glow-wire test at 550 °C according to IEC 60695-2-11 is acceptable as an alternative.	EL 2124-08		
	c) Where it is not practical to protect components against overheating under fault conditions, the components shall be mounted on V-1 CLASS MATERIAL. Additionally, such components shall be separated from material of a class lower than V-1 CLASS MATERIAL by at least 13 mm of air, or by a solid barrier of V-1 CLASS MATERIAL.	EL 2124-09		
4.7.3.2	Materials for fire enclosures			
	a) For MOVABLE EQUIPMENT having a total mass not exceeding 18 kg, the material of a FIRE ENCLOSURE, in the thinnest significant wall thickness used, shall be of V-1 CLASS MATERIAL or shall pass the test of Clause A.2.	EL 2124-10		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 43 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

	b) For MOVABLE EQUIPMENT having a total mass exceeding 18 kg and for all STATIONARY EQUIPMENT, the material of a FIRE ENCLOSURE, in the thinnest significant wall thickness used, shall be of 5VB CLASS MATERIAL or shall pass the test of Clause A.1.	EL 2124-11	
	c) Materials for components that fill an opening in a FIRE ENCLOSURE, and that are intended to be mounted in this opening shall: be of V-1 CLASS MATERIAL; or pass the tests of Clause A.2; or comply with the flammability requirements of the relevant IEC component standard	EL 2124-12	
	d) Plastic materials of a FIRE ENCLOSURE shall be located more than 13 mm through air from arcing parts such as unenclosed commutators and unenclosed switch contacts.	EL 2124-13	
	e)Plastic materials of a FIRE ENCLOSURE located less than 13mm through air from non-arcing parts which, under any condition of normal or abnormal operation, could attain a temperature sufficient to ignite the material, shall be capable of passing the test of IEC 60695-2-20. The average time to ignition of the samples shall be not less than 15sec. If the sample melts through without igniting, the time at which this occurs is not considered to be the time to	EL 2124-14	
	ignition.		
4.7.3.3	Materials for components and other parts outside fire enclosures *		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 44 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

	a) Materials shall be of : - HB75 CLASS MATERIAL if the thinnest significant thickness of this material is < 3 mm, or - HB40 CLASS MATERIAL if the thinnest significant thickness of this material is ≥ 3 mm, or - HBF CLASS FOAMED MATERIAL.*	EL 2124-15	
	b) Connectors shall comply with one of the following: - be made of V-2 CLASS MATERIAL; or - pass the tests of Clause A.2; or - comply with the flammability	EL 2124-16	
	requirements of the relevant IEC component standard; or – be mounted on V-1 CLASS MATERIAL and be of a small size; or		
	be located in a SECONDARY CIRCUIT supplied by a power source that is limited to a maximum of 15 VA (see 1.4.11) under normal operating conditions and after a single fault		
	in the equipment (see 1.4.14).		
4.7.3.4	Materials for components and other parts inside fire enclosures		
	a) Inside FIRE ENCLOSURES, materials for components and other parts shall comply with	EL 2124-17	
	one of the following: - be of V-2 CLASS MATERIAL or HF-2 CLASS FOAMED		
	MATERIAL; or – pass the flammability test described in Clause A.2; or		
	- meet the flammability requirements of a relevant IEC component standard that includes such requirements.		
	Requirements for voltage dependent resistors (VDR's) are in Annex Q.*	EL 2124-18	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 45 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

4.7.3.5	Materials for air filter assemblies	FL 2124-19	
4.7.3.3	:	EL 2124-19	
	Air filter assemblies shall be		
	constructed of V-2 CLASS MATERIAL, or HF-2 CLASS		
	FOAMED		
	MATERIAL.		
4.7.3.6	Materials used in high-voltage components		
	a) High-voltage components operating at peak-to-peak voltages exceeding 4 kV shall either be	EL 2124-20	
	of V-2 CLASS MATERIAL, or		
	HF-2 CLASS FOAMED		
	MATERIAL, or comply with 14.4 of IEC 60065 or		
	pass the needle flame test according to IEC 60695-11-5.		
	b) Compliance is checked by inspection of the equipment and material data sheets and, if	EL 2124-21	
	necessary, by		
	- the tests for V-2 CLASS MATERIAL or HF-2 CLASS FOAMED MATERIAL; or		
	- the test described in 14.4 of IEC 60065; or		
	- the needle flame test according to IEC 60695-11-5.		
	c) In addition to above, the following details apply, referring to clauses of IEC 60695-11-5:	EL 2124-22	
	Clause 7 - Severities		
	Clause 8 - Conditioning	EL 2124-23	
	Clause 11 - Evaluation of test results	EL 2124-24	

*- Total number of Requirements to be observed / inspected =
Total No of applicable Requirement =
No of Requirements for which the sample passed=

Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample passe	d=
Certificate: It is certified that the above trequirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 46 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Insulating Properties

EL 2125 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
5.0	ELECTRICAL REQUIREMENTS AND SIMULATED ABNORMAL CONDITIONS*	EL 2125-00		
5.1	Touch current and protective conductor current*	EL 2125-01		
5.1.2	Configuration of equipment under test (EUT)*	EL 2125-02		
5.1.2.1	Single connection to an a.c. mains supply*	EL 2125-03		
5.1.2.2	Redundant multiple connections to an a.c. mains supply*	EL 2125-04		
5.1.2.3	Simultaneous multiple connections to an a.c. mains supply	EL 2125-05		
5.1.3	Test circuit	EL 2125-06		
5.1.4	Application of measuring instrument	EL 2125-07		
5.1.5	Test procedure	EL 2125-08		
5.1.6	Test measurements			
	a) r.m.s value of voltage, U2 measured using the instrument as per Fig. D.1 or r.m.s value of current measured using the instrument as per Fig. D.2	EL 2125-09		
	Alternatively, peak value of voltage, U2, is measured using the measuring instrument described in Clause D.1			
	b) Measured touch current (mA):	EL 2125-10		
	c) Calculated value of TOUCH CURRENT (mA) = U2 / 500	EL 2125-11		
	d) Measured protective conductor current(mA)	EL 2125-12		
	e) Max. protective conductor current =5% of Input current	EL 2125-13		
5.1.7	Equipment with touch current exceeding 3.5 mA	EL 2125-14		
5.1.7.1	General	EL 2125-15		
5.1.7.2	Simultaneous multiple connections to the supply	EL 2125-16		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 47 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

5.1.8	Touch currents to telecommunication networks and cable distribution systems and from telecommunication networks	EL 2125-17	
5.1.8.1	Limitation of the touch current to a telecommunication network or to a cable distribution system	EL 2125-18	
	Supply voltage (V)		
	Measured touch current (mA)		
	Max. allowed touch current (mA)		
5.1.8.2	Summation of touch currents from telecommunication networks	EL 2125-19	
	a) EUT with earthed telecommunication ports :		
	b) EUT whose telecommunication ports have no reference to protective earth		

	b) EUT whose telecommunication ports have no reference to protective earth		
Total No	nber of Requirements to be obsert of applicable Requirement equirements for which the sample	·	d = =
Total No of	er of tests to be conducted = applicable Tests = for which the sample passed=		
Certificate: requiremer		were performe	d and found to be passing/failing in the
(Approving	Authority)		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 48 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Insulating Properties

EL 2126 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
5.2	Electric strength*	EL 2126-00		
5.2.1	General*	EL 2126-01		
5.2.2	Test procedure			
	a) The test voltages for electric strength for the appropriate grade of insulation [FUNCTIONAL	EL 2126-02		
	INSULATION if required by 5.3.4 b), BASIC INSULATION, SUPPLEMENTARY INSULATION or			
	REINFORCED INSULATION] are as specified in either:			
	 Table 5B using the PEAK WORKING VOLTAGE (U), as determined in 2.10.2; or 			
	 Table 5C using the REQUIRED WITHSTAND VOLTAGE, as determined in G.4. 			

*- Total number of Requirements to be observed / inspected Total No of applicable Requirement No of Requirements for which the sample passed=	I = =
Total number of tests to be conducted =	
Total No of applicable Tests =	
No. of tests for which the sample passed=	
Certificate: It is certified that the above tests were performed requirement tested.	d and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 49 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Insulating Properties

EL 2127 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
5.3	Abnormal operating and fault conditions	EL 2127-00		
5.3.1	Protection against overload and abnormal operation	EL 2127-01		
5.3.2	Motors	EL 2127-02		
5.3.3	Transformers	EL 2127-03		
5.3.4	Functional insulation:	EL 2127-04		
5.3.5	Electromechanical components	EL 2127-05		
5.3.6	Audio amplifiers in ITE :	EL 2127-06		
5.3.7	Simulation of faults	EL 2127-07		
5.3.8	Unattended equipment	EL 2127-08		
5.3.9	Compliance criteria for abnormal operating and fault conditions*			
5.3.9.1	During the tests	EL 2127-09		
5.3.9.2	After the tests	EL 2127-10		

			1	
5.3.9.2	After the tests	EL 2127-10		
*- Total nur	mber of Requirements to be obser	rved / inspecte	d =	
Total No	of applicable Requirement		=	
No of Re	equirements for which the sample	passed=		
Total numb	er of tests to be conducted =			
Total No of	applicable Tests =			
No. of tests	for which the sample passed=			
Certificate: requiremer		were performe	ed and found to be passing/failing in the	
(Approving	Authority)			

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 50 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Communicating Connection

EL 2128 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
6.1	Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment	EL 2128-00		
6.1.1	Protection from hazardous voltages	EL 2128-01		
6.1.2	Separation of the telecommunication network from earth*			
6.1.2.1	Requirements: - Surge suppressors that bridge the insulation shall have a minimum rated operating voltage U _{op} of U _{op} =U _{peak} + ΔU _{sp} + ΔU _{sa} Where U _{peak} is 360V or 180V ΔU _{sp} is the maximum increase of the rated operating voltage due to variations in component production(If not specified by the manufacturer, shall be taken as 10% of the rated operating voltage of the component) ΔU _{sa} is the maximum increase of the rated operating voltage due to the component ageing over the expected life of the equipment(If not specified by the manufacturer, shall be taken as 10% of the rated operating voltage of the component) -Insulation is subjected to electric strength test according to 5.2.2. The a.c test voltage is 1.5kV or 1.0kV - Components bridging the insulation that are left in place during electric strength testing shall not be damaged. There shall be no breakdown of insulation during electric strength testing.			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 51 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
6.1.2.2	Exclusions	EL 2128-03		

*- Total number of Requirements to be	observed / inspected =
Total No of applicable Requirement	=
No of Requirements for which the sa	mple passed=
Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample passe	d=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 52 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Communicating Connection

EL 2129 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
6.2	Protection of equipment users from overvoltages on telecommunication networks*	EL 2129-00		
6.2.1	Separation requirements	EL 2129-01		
6.2.2	Electric strength test procedure	EL 2129-02		
6.2.2.1	Impulse test	EL 2129-03		
6.2.2.2	Steady-state test	EL 2129-04		
6.2.2.3	Compliance criteria	EL 2129-05		

*- Total number of Requirements to be a Total No of applicable Requirement No of Requirements for which the sai	· =
Total number of tests to be conducted Total No of applicable Tests No. of tests for which the sample passe	= = d=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 53 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Communicating Connection

EL 2130 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
6.3	Protection of the telecommunication wiring system from overheating	EL 2130-00		
	a)If current limiting is due to the inherent impedance of the power source, the output current into any resistive load, including a short-circuit, is measured. The current limit shall not be exceeded after 60 s of test. Max. output current (A):	EL 2130-01		
	b) If current limiting is provided by an overcurrent protective device having a specified time/current characteristic: - the time/current characteristic shall show that a current equal to 110 % of the current limit will be interrupted within 60 min; and	EL 2130-02		
	c) the output current into any resistive load, including a short-circuit, with the overcurrent protective device bypassed, measured after 60 s of test, shall not exceed 1 000/U,	EL 2130-03		
	where U is the output voltage measured in accordance with 1.4.5 with all load circuits disconnected.			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 54 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

d) If current limiting is provided by an overcurrent protective device that does not have a specified time/current	EL 2130-04	
characteristic:		
 the output current into any resistive load, including a short- circuit, shall not exceed the 		
current limit after 60 s of test; and		
 the output current into any resistive load, including a short- circuit, with the overcurrent 		
protective device bypassed, measured after 60 s of test, shall not exceed 1 000/U, where		
U is the output voltage measured in accordance with 1.4.5 with all load circuits		
disconnected.		

*- Total number of Requirements to be observed / inspected =
Total No of applicable Requirement =
No of Requirements for which the sample passed=

Total number of tests to be conducted = Total No of applicable Tests = No. of tests for which the sample passed=

Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.

(Approving Authority)

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 55 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Connection to cable distribution system

EL 2131 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
7	Connection to cable distribution systems*	EL 2131-00		
7.1	General requirements*	EL 2131-01		
7.2	Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous voltages in the equipment	EL 2131-02		
7.3	Protection of equipment users from overvoltages on the cable distribution system	EL 2131-03		
7.4	Insulation between primary circuits and cable distribution systems	EL 2131-04		
7.4.1	General	EL 2131-05		
7.4.2	Voltage surge test	EL 2131-06		
7.4.3	Impulse test	EL 2131-07		

*- Total number of Requirements to be Total No of applicable Requirement	observed / inspected = = =
No of Requirements for which the sa	mple passed=
Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample passe	ed=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 56 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Fire Safety

EL 2132 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
А	ANNEX A, TESTS FOR RESISTANCE TO HEAT AND FIRE	EL 2132-00		
A.1	Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2)	EL 2132-01		
A.1.1	Samples:	EL 2132-02		
	Wall thickness (mm):			
A.1.2	Conditioning of samples; temperature (°C):	EL 2132-03		
A.1.3	Mounting of samples :	EL 2132-04		
A.1.4	Test flame (see IEC 60695-11-3)	EL 2132-05		
	Flame A, B, C or D:			
A.1.5	Test procedure	EL 2132-06		
A.1.6	Compliance criteria	EL 2132-07		
	Sample 1 burning time (s):			
	Sample 2 burning time (s):			
	Sample 3 burning time (s):			
A.2	Flammability test for fire enclosures of movable equipment having a total mass not exceeding 18 kg, and for material and components located inside fire enclosures (see 4.7.3.2 and 4.7.3.4)	EL 2132-08		
A.2.1	Samples, material:	EL 2132-09		
	Wall thickness (mm):			
A.2.2	Conditioning of samples; temperature (°C):	EL 2132-10		
A.2.3	Mounting of samples :	EL 2132-11		
A.2.4	Test flame (see IEC 60695-11-4)	EL 2132-12		
	Flame A, B or C:			
A.2.5	Test procedure	EL 2132-13		
A.2.6	Compliance criteria	EL 2132-14		
	Sample 1 burning time (s):			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 57 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Fire Safety

EL 2132 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
	Sample 2 burning time (s):			
	Sample 3 burning time (s):			
A.2.7	Alternative test acc. to IEC 60695-11-5, cl. 5 and 9	EL 2132-15		
	Sample 1 burning time (s):			
	Sample 2 burning time (s):			
	Sample 3 burning time (s):			
A.3	Hot flaming oil test (see 4.6.2)	EL 2132-16		
A.3.1	Mounting of samples	EL 2132-17		
A.3.2	Test procedure	EL 2132-18		
A.3.3	Compliance criterion	EL 2132-19		

	•		
* T. t. I	al an of Demain manufacture.		
"- Total nur	nber of Requirements to be ob	servea / inspecte	a =
Total No	of applicable Requirement		=
No of Re	quirements for which the samp	le passed=	
Total numb	er of tests to be conducted =		
Total No of	applicable Tests =		
No. of tests	for which the sample passed=		
Certificate: requiremen		ts were performe	ed and found to be passing/failing in the
(Approving	Authority)		

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 58 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Insulating Properties

EL 2133 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
В	ANNEX B, MOTOR TESTS UNDER ABNORMAL CONDITIONS (see 4.7.2.2 and 5.3.2)	EL 2133-00		
B.1	General requirements	EL 2133-01		
	Position :			
	Manufacturer :			
	Type:			
	Rated values :			
B.2	Test conditions	EL 2133-02		
B.3	Maximum temperatures	EL 2133-03		
B.4	Running overload test	EL 2133-04		
B.5	Locked-rotor overload test	EL 2133-05		
	Test duration (days):			
	Electric strength test: test voltage (V):			
B.6	Running overload test for d.c. motors in secondary circuits	EL 2133-06		
B.6.1	General	EL 2133-07		
B.6.2	Test procedure	EL 2133-08		
B.6.3	Alternative test procedure	EL 2133-09		
B.6.4	Electric strength test; test voltage (V):	EL 2133-10		
B.7	Locked-rotor overload test for d.c. motors in secondary circuits	EL 2133-11		
B.7.1	General	EL 2133-12		
B.7.2	Test procedure	EL 2133-13		
B.7.3	Alternative test procedure	EL 2133-14		
B.7.4	Electric strength test; test voltage (V) :	EL 2133-15		
B.8	Test for motors with capacitors	EL 2133-16		
B.9	Test for three-phase motors	EL 2133-17		
B.10	Test for series motors	EL 2133-18		
	Operating voltage (V):			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 59 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

*- Total number of Requirements to be o Total No of applicable Requirement No of Requirements for which the san	· =
Total number of tests to be conducted Total No of applicable Tests No. of tests for which the sample passed	= = d=
Certificate: It is certified that the above to requirement tested.	ests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 60 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Electrical Safety

EL 2134 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
С	ANNEX C, TRANSFORMERS (see 1.5.4 and 5.3.3)*	EL 2134-00		
	Position :			
	Manufacturer :			
	Type:			
	Rated values :			
	Method of protection:			
C.1	Overload test	EL 2134-01		
C.2	Insulation	EL 2134-02		
	Protection from displacement of windings:			

windings:		
*- Total number of Requirements to be obser Total No of applicable Requirement No of Requirements for which the sample	·	d = =
Total number of tests to be conducted =		
Total No of applicable Tests =		
No. of tests for which the sample passed=		
Certificate: It is certified that the above tests requirement tested.	were performe	d and found to be passing/failing in the
(Approving Authority)		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 61 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Insulating Properties

EL 2135 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
D	ANNEX D, MEASURING INSTRUMENTS FOR TOUCH- CURRENT TESTS (see 5.1.4)	EL 2135-00		
D.1	Measuring instrument	EL 2135-01		
D.2	Alternative measuring instrument	EL 2135-02		

	instrument			
Total No	nber of Requirements to be obser of applicable Requirement quirements for which the sample	·	d = =	
Total No of	er of tests to be conducted = applicable Tests = for which the sample passed=			
Certificate: equiremen		were performe	d and found to be passing/failing in the	
(Approving	Authority)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 62 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Thermal Properties

EL 2136- V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
E	ANNEX E, TEMPERATURE RISE OF A WINDING (see 1.4.13)	EL2136-00		

1	.4.13)			
Total No o	per of Requirements to be obser f applicable Requirement uirements for which the sample	·	d = =	
Total No of a	r of tests to be conducted = pplicable Tests = or which the sample passed=			
Certificate: It requirement		were performe	d and found to be passing/failing in the	
(Approving A	uthority)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 63 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2137 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
F	ANNEX F, MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES (see 2.10 and Annex G)	EL2137-00		

*- Total number of Requirements to be observed / inspected = Total No of applicable Requirement = No of Requirements for which the sample passed=
Total number of tests to be conducted =
Total No of applicable Tests =
No. of tests for which the sample passed=
Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.
(Approving Authority)

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 64 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Electrical safety

EL 2138 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
G	ANNEX G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES	EL 2138-00		
G.1	Clearances	EL 2138-01		
G.1.1	General	EL 2138-02		
G.1.2	Summary of the procedure for determining minimum clearances	EL 2138-03		
G.2	Determination of mains transient voltage (V)	EL 2138-04		
G.2.1	AC Mains supply	EL 2138-05		
G.2.2	Earthed d.c. mains supplies	EL 2138-06		
G.2.3	Unearthed d.c. mains supplies	EL 2138-07		
G.2.4	Battery operation	EL 2138-08		
G.3	Determination of telecommunication network transient voltage (V)	EL 2138-09		
G.4	Determination of required withstand voltage (V)	EL 2138-10		
G.4.1	Mains transients and internal repetitive peaks	EL 2138-11		
G.4.2	Transients from telecommunication networks:	EL 2138-12		
G.4.3	Combination of transients	EL 2138-13		
G.4.4	Transients from cable distribution systems	EL 2138-14		
G.5	Measurement of transient voltages (V)	EL 2138-15		
	a) Transients from a mains supply			
	For an a.c. mains supply			
	For a d.c. mains supply			
	b) Transients from a telecommunication network			
G.6	Determination of minimum clearances	EL 2138-16		

^{*-} Total number of Requirements to be observed / inspected =
Total No of applicable Requirement =
No of Requirements for which the sample passed=

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 65 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Total number of tests to be conducted Total No of applicable Tests No. of tests for which the sample passe	= = d=
Certificate: It is certified that the above tequirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 66 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Radiation Safety

EL 2139 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
Н	ANNEX H, IONIZING RADIATION (see 4.3.13)	EL 2139-00		

*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sa	· =
Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample passe	d=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 67 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2140 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
J	ANNEX J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6)*	EL 2140-00		
	Metal(s) used :			

*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sa	· =
Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample passe	ed=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 68 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to General Requirement

EL 2141 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
К	ANNEX K, THERMAL CONTROLS (see 1.5.3 and 5.3.8)*	EL 2141-00		
K.1	Making and breaking capacity	EL 2141-01		
K.2	Thermostat reliability; operating voltage (V) :	EL 2141-02		
K.3	Thermostat endurance test; operating voltage (V):	EL 2141-03		
K.4	Temperature limiter endurance; operating voltage (V) :	EL 2141-04		
K.5	Thermal cut-out reliability	EL 2141-05		
K.6	Stability of operation	EL 2141-06		

K.6	Stability of operation	EL 2141-06		
Total No	mber of Requirements to be obsort of applicable Requirement equirements for which the sample	·	d = =	
Total No of	er of tests to be conducted = applicable Tests = for which the sample passed=			
Certificate: requiremer		s were performe	ed and found to be passing/failing in the	
(Approving	Authority)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 69 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to General Requirement

EL 2142 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
L	ANNEX L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.2)*	EL 2142-00		
L.1	Typewriters*	EL 2142-01		
L.2	Adding machines and cash registers*	EL 2142-02		
L.3	Erasers*	EL 2142-03		
L.4	Pencil sharpeners*	EL 2142-04		
L.5	Duplicators and copy machines*	EL 2142-05		
L.6	Motor-operated files*	EL 2142-06		
L.7	Other business equipment*	EL 2142-07		

*- Total nur	mber of Requirements to be	obser	ved / inspected	d =	
Total No	of applicable Requirement			=	
No of Re	quirements for which the sai	mple	passed=		
Total numb	er of tests to be conducted	=			
Total No of	applicable Tests	=			
No. of tests	for which the sample passe	d=			
Certificate: requiremen		tests v	were performe	d and found to be passing/failing in the	
(Approving	Authority)				

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 70 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Electrical Safety

EL 2143 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
М	ANNEX M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)	EL 2143-00		
M.1	Introduction*	EL 2143-01		
M.2	Method A	EL 2143-02		
M.3	Method B	EL 2143-03		
M.3.1	Ringing signal	EL 2143-04		
M.3.1.1	Frequency (Hz)	EL 2143-05		
M.3.1.2	Voltage (V)	EL 2143-06		
M.3.1.3	Cadence; time (s), voltage (V)	EL 2143-07		
M.3.1.4	Single fault current (mA)	EL 2143-08		
M.3.2	Tripping device and monitoring voltage	EL 2143-09		
M.3.2.1	Conditions for use of a tripping device or a monitoring voltage	EL 2143-10		
M.3.2.2	Tripping device	EL 2143-11		
M.3.2.3	Monitoring voltage (V)	EL 2143-12		

*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sa	· =
Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample pass	ed=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 71 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical safety

EL 2144 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
N	ANNEX N, IMPULSE TEST GENERATORS (see 1.5.7.2, 1.5.7.3, 2.10.3.9, 6.2.2.1, 7.3.2, 7.4.3 and Clause G.5)	EL 2144-00		
N.1	ITU-T impulse test generators	EL 2144-01		
N.2	IEC 60065 impulse test generator	EL 2144-02		

*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sa	· =	
Total number of tests to be conducted	=	
Total No of applicable Tests	=	
No. of tests for which the sample passe	ed=	
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in	ı the
(Approving Authority)		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 72 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to General Requirements

EL 2145- V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
Р	ANNEX P, NORMATIVE REFERENCES	EL 2145-00		

*- Total number of Requirements to be	observed / inspected =
Total No of applicable Requirement	=
No of Requirements for which the sa	mple passed=
Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample passe	ed=
Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.	
(Approving Authority)	

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 73 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to General Requirements

TRF No. BIS_IT/PR_IS13252_V1.2

EL 2146 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
Q	ANNEX Q, Voltage dependent resistors (VDRs) (see 1.5.9.1)	EL 2146-00		
	A VDR shall comply with iec 61051-2, whether a fire enclosure is provided or not, taking into account all of the following:			
	a) Preferred climatic categories			
	Lower category temperature: -10°C			
	Upper category temperature: +85°C			
	Duration of damp Test, steady state test:21 days			
	b) Maximum continuous voltage:			
	Atleast 1,25 times the rated voltage of the equipment or			
	Atleast 1,25 times the upper voltage of the rated voltage range			
	c) Combination pulse :	EL 2146-01		
	d) Body of the VDR shall comply with Needle flame test according to IEC 60695-11-5 with the following test severities:	EL 2146-02		
	duration of application of the test flame: 10 s			
	after flame time: 5s			
	[This test is not required if VDR complies with V-1 CLASS MATERIAL]			

'- Total nur	nber of Requirements to be obser	ved / inspected	d =		
Total No	of applicable Requirement		=		
No of Re	equirements for which the sample	passed=			
Total numb	er of tests to be conducted =				
Total No of	applicable Tests =				
No. of tests	for which the sample passed=				
	ertificate: It is certified that the above tests were performed and found to be passing/failing in the equirement tested.				
(Approving	Authority)				

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 74 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

EL 2147- V1.4

Tests relating to General Requirement

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
R	ANNEX R, EXAMPLES OF REQUIREMENTS FOR QUALITY CONTROL PROGRAMMES*	EL 2147-00		
R.1	Minimum separation distances for unpopulated coated printed boards (see 2.10.6.2)*	EL 2147-01		
R.2	Reduced clearances (see 2.10.3)*	EL 2147-02		

N.Z	2.10.3)*	EL 2147-02	
*- Total nu	mber of Requirements to be obse	rved / inspecte	d =
	of applicable Requirement	•	=
No of Re	equirements for which the sample	passed=	
Total numb	per of tests to be conducted =		
Total No of	f applicable Tests =		
No. of tests	s for which the sample passed=		
Certificate: requiremen		were performe	d and found to be passing/failing in the
(Approving	Authority)		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 75 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to General Requirement

EL 2148 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
S	ANNEX S, PROCEDURE FOR IMPULSE TESTING (see 6.2.2.3)*	EL 2148-00		
S.1	Test equipment*	EL 2148-01		
S.2	Test procedure*	EL 2148-02		
S.3	Examples of waveforms during impulse testing*	EL 2148-03		

*- Total number of Requirements to be ob- Total No of applicable Requirement No of Requirements for which the sam	· =
Total number of tests to be conducted Total No of applicable Tests =	= : -
	= sts were performed and found to be passing/failing in the
requirement tested. (Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 76 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

EL 2149 - V1.4

Tests relating to Protection against Ingress of water

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
Т	ANNEX T, GUIDANCE ON PROTECTION AGAINST INGRESS OF WATER (see 1.1.2)*	EL 2149-00		

	INGRESS OF WATER (see 1.1.2)*			
Total No	nber of Requirements to be obse of applicable Requirement equirements for which the sample	·	d = =	
Total No of	er of tests to be conducted = applicable Tests = for which the sample passed=			
Certificate: requiremer		were performe	ed and found to be passing/failing in the	
(Approving	Authority)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 77 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

EL 2150 - V1.4

Tests relating to Wiring

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
U	ANNEX U, INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION (see 2.10.5.4)	EL2150-00		
U.1	GENERAL	EL2150-01		
U.2	TYPE TESTS	EL2150-02		
U.2.1	GENERAL	EL2150-03		
U.2.2	ELECTRIC STRENGTH	EL2150-04		
U.2.2.1	SOLID ROUND WINDING WIRE AND STRANDED WINDING WIRES	EL2150-05		
U.2.2.1.1	WIRES WITH NOMINAL CONDUCTOR DIAMETER UPTO AND INCLUDING 0.100MM	EL2150-06		
U.2.2.1.2	WIRES WITH NOMINAL CONDUCTOR DIAMETER OVER 0.100MM AND INCLUDING 2.500MM	EL2150-07		
U.2.2.1.3	WIRES WITH NOMINAL CONDUCTOR DIAMETER OVER 2.500MM	EL2150-08		
U.2.2.2	SQUARE OR RECTANGULAR WIRES	EL2150-09		
U.2.3	FLEXIBILITY AND ADHERENCE	EL2150-10		
U.2.4	HEAT SHOCK	EL2150-11		
U.2.5	RETENTION OF ELECTRIC STRENGTH AFTER BENDING	EL2150-12		
U.3	TESTING DURING MANUFACTURING	EL2150-13		
U.3.1	GENERAL	EL2150-14		
U.3.2	ROUTINE TESTS	EL2150-15		
U.3.3	SAMPLING TEST	EL2150-16		

^{*-} Total number of Requirements to be observed / inspected = Total No of applicable Requirement =

No of Requirements for which the sample passed=
Total number of tests to be conducted =

Total No of applicable Tests =

No. of tests for which the sample passed=

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 78 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.

.....

(Approving Authority)

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 79 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2151 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
V	ANNEX V, AC POWER DISTRIBUTION SYSTEMS (see 1.6.1) *	EL 2151-00		
V.1	Introduction*	EL 2151-01		
V.2	TN power distribution systems	EL 2151-02		
V.3	TT Power Distribution systems	EL 2151-03		
V.4	IT Power Distribution systems	EL 2151-04		

*- Total number of Requirements to be	observed / inspected	d =
Total No of applicable Requirement		=
No of Requirements for which the sa	ample passed=	
Total number of tests to be conducted	=	
Total No of applicable Tests	=	
No. of tests for which the sample passe	ed=	
Certificate: It is certified that the above requirement tested.	tests were performe	d and found to be passing/failing in the
. oquoc. tootou.		
(Approving Authority)		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 80 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2152 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
W	ANNEX W, SUMMATION OF TOUCH CURRENTS *	EL 2152-00		
W.1	Touch current from electronic circuits*	EL 2152-01		
W.1.1	Floating circuits*	EL 2152-02		
W.1.2	Earthed circuits*	EL 2152-03		
W.2	Interconnection of several equipments*	EL 2152-04		
W.2.1	Isolation*	EL 2152-05		
W.2.2	Common return, isolated from earth*	EL 2152-06		
W.2.3	Common return, connected to protective earth*	EL 2152-07		

1			1	
W.2.3	Common return, connected to protective earth*	EL 2152-07		
*- Total nur	mber of Requirements to be obser	ved / inspected	d =	
Total No	of applicable Requirement	•	=	
	equirements for which the sample	nassed=		
140 01 140	equirements for which the sample	passeu-		
Total numb	er of tests to be conducted =			
Total No of	applicable Tests =			
No. of tests	for which the sample passed=			
Certificate: requiremer		were performe	d and found to be passing/failing in the	
(Approving	Authority)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 81 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

EL 2153- V1.4

Tests relating to Electrical Safety

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
X	ANNEX X, MAXIMUM HEATING EFFECT IN TRANSFORMER TESTS (see clause C.1)*	EL 2153-00		
X.1	Determination of maximum input current*	EL 2153-01		
X.2	Overload test procedure*	EL 2153-02		

*- Total number of Requirements to be Total No of applicable Requirement No of Requirements for which the sa	· =
Total number of tests to be conducted	=
Total No of applicable Tests	=
No. of tests for which the sample passe	ed=
Certificate: It is certified that the above requirement tested.	tests were performed and found to be passing/failing in the
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 82 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Radiation Safety

EL 2154- V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
Υ	ANNEX Y, ULTRAVIOLET LIGHT CONDITIONING TEST (see 4.3.13.3)	EL 2154-00		
Y.1	Test apparatus	EL 2154-01		
Y.2	Mounting of test samples	EL 2154-02		
Y.3	Carbon-arc light-exposure apparatus	EL 2154-03		
Y.4	Xenon-arc light exposure apparatus	EL 2154-04		

*- Total number of Requirements to be o	bserved / inspected =
Total No of applicable Requirement	=
No of Requirements for which the same	pple passed=
Total number of tests to be conducted	=
Total No of applicable Tests =	=
No. of tests for which the sample passed	=
Certificate: It is certified that the above te requirement tested.	ests were performed and found to be passing/failing in the
(A	
(Approving Authority)	

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 83 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

EL 2155- V1.4

Tests relating to Electrical Safety

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
Z	ANNEX Z, OVERVOLTAGE CATEGORIES (see 2.10.3.2 and Clause G.2)*	EL 2155-00		

	and Clause G.2)*			
Total No	nber of Requirements to be obser of applicable Requirement quirements for which the sample	·	d = =	
Total No of	er of tests to be conducted = applicable Tests = for which the sample passed=			
Certificate: requiremen		were performe	d and found to be passing/failing in the	
(Approving	Authority)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 84 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Mechanical Properties

EL 2156 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
AA	ANNEX AA, MANDREL TEST (see 2.10.5.8)	EL 2156-00		

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdi
AA	ANNEX AA, MANDREL TEST (see 2.10.5.8)	EL 2156-00		
Total No	nber of Requirements to be obser of applicable Requirement quirements for which the sample	·	d = =	
Total No of	er of tests to be conducted = applicable Tests = for which the sample passed=			
Certificate: requiremen		were performe	d and found to be passing/failing in the	
(Approving	Authority)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 85 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Electrical Safety

EL 2158 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
CC	Evaluation of integrated circuit (IC) current limiters*	EL 2158-00		
CC.1	Integrated circuit (IC) current limiters*	EL 2158-01		
CC.2	Test program 1	EL 2158-02		
CC.3	Test program 2	EL 2158-03		
CC.4	Test program 3	EL 2158-04		
CC.5	Compliance	EL 2158-05		

*- Total number of Requirements to be observed / inspected =
Total No of applicable Requirement =
No of Requirements for which the sample passed=

Total number of tests to be conducted =
Total No of applicable Tests =
No. of tests for which the sample passed=

Certificate: It is certified that the above tests were performed and found to be passing/failing in the requirement tested.

(Approving Authority)

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 86 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

Tests relating to Mechanical Properties

EL 2159 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
DD	Requirements for the mounting means of rack-mounted equipment*	EL 2159-00		
DD.1	General			
DD.2	Mechanical strength test, variable N	EL 2159-01		
DD.3	Mechanical strength test, 250N, including end stops	EL 2159-02		
DD.4	Compliance*:	EL 2159-03		

	1		
DD.4	Compliance*:	EL 2159-03	
Total No	mber of Requirements to be obse of applicable Requirement equirements for which the sample	•	d = =
Total No of	per of tests to be conducted = f applicable Tests = s for which the sample passed=		
Certificate: requiremer		s were performe	ed and found to be passing/failing in the
(Approving	Authority)		

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 87 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

Tests relating to Mechanical Properties

EL 2160 - V1.4

Cl. No.	Test / Requirement name	Test Code	Test result/ observation	Verdict
EE	ANNEX EE, Household and home/office document/media shredders	EL 2160-00		
EE.1	General			
EE.2	Markings and instructions*	EL 2160-01		
	Use of markings or symbols*:			
	Information of user instructions, maintenance and/or servicing instructions*			
EE.3	Inadvertent reactivation test	EL 2160-02		
EE.4	Disconnection of power to hazardous moving parts*	EL 2160-03		
	Use of markings or symbols*:			
EE.5	Protection against hazardous moving parts			
	Test with test finger (Figure 2A)	EL 2160-04		
	Test with wedge probe (Figure EE1 and EE2):	EL 2160-05		

	EE1 and EE2):	LL 2100-03		
*- Total nur	nber of Requirements to be obse	rved / inspecte	d =	
Total No	of applicable Requirement		=	
No of Re	quirements for which the sample	passed=		
Total numb	er of tests to be conducted =			
Total No of	applicable Tests =			
	for which the sample passed=			
Certificate: requiremen		were performe	d and found to be passing/failing in the	
(Approving	Authority)			

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 88 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

1.5.1	TAB	BLE: List of components									
Object/part no.		Manufacturer/ trademark	Type/model	Technical data Standard		Mark(s) of conformity					
Supplement	Supplementary information:										

1.6.2	TABLE: El	TABLE: Electrical data (in normal conditions)							
U (V)	I (A)	Irated (A)	P (W)	Fuse #	Ifuse (A)	Condition/status			
Supplemen	Supplementary information:								

2.1.1.5	TABLE:	TABLE: Energy hazard measurement						
Voltage ((V)	rated)	Current (rated) (A)	Voltage (max.) (V)	Current (max.) (A)	VA (max.) (VA)			
Supplement	Supplementary information:							

2.1.1.7	TABLE: [BLE: Discharge test							
Condition		τ calculated (s)	τ measured (s)	t u→ 0V (s)	Comments				
Supplement	Supplementary information:								

2.2.2	TABLE: S	BLE: SELV measurement (under normal conditions)						
Transformer		Location	Voltage (max.) (V)	Voltage Limitation	n			

Report No.	XXXXXX	IS	13252	(Part 1): 201	10 + A1:	20	13 + A2 : 201	5 /	Page	e 89 of 95
Dated: xxxx	«хх		IEC 60	950-1: 2005	5 + A1:20	200	9 + A2 : 2013			
							1		0	
					V peak		V d.c.		Component	
Supplement	ary information	า:								
	T .									
2.2.3	TABLE: SELV	/ measu		•						
Location			Vo	ltage (max.)	(V) (Cor	mments			
Supplement	ary information	n :								
0.4.0										
2.4.2	TABLE: Limite						1.514		 .	
Location		Volta (V		Current (mA)	Freq (kHz		Limit (mA)	Cor	mments	
Supplement	ary information	า:								
2.5	TABLE: Limite	ed powe	r sourc	e measurem	ent					
				Limits			N	/leas	ured	Verdict
According to	Table 2B/2C	(normal	condit	ion)						•
current (in A	۸)									
apparent po	wer (in VA)									
According to	Table 2B/2C	(single f	ault co	ndition)						1
current (in A	۸)									
apparent po	wer (in VA)									
Supplement	ary information	า:					<u> </u>			
2.6.3.4	TABLE: Resis	stance of	earthi	ng measurer	nent					
Location			Resis	tance meası	ıred (mΩ	2)	Comments			
						1				
						1				
Supplement	ary information	n: Teste	d curre	nt 32A.						

						[L	AB LOGO
Report No. xxxxxx	IS 13252 (Pa	art 1): 2010) + A1: 201	13 + A2	: 2015/	Pa	ge 90 of 95
Dated: xxxxxx	IEC 6095	0-1: 2005	+ A1:2009	+ A2 : 2	2013		
<or></or>							
2.6.3.4 TABLE: Resistance	e of earthing i	measurem	ent				
Location	Vol	ltage drop	(V)	Commer	nts		
Supplementary information: Te	sted current 3	32A.					
2.10.2 Table: Working vo	ltogo massim	omon ⁴					
2.10.2 Table: Working vo		ltage (V)	Peak volta	200 (\/)	Commer	nte.	
Location	TAIVIS VO	mage (v)	reak voice	age (v)	Comme	iis	
Supplementary information:							
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,							
2.10.3 and 2.10.4 TABLE: Clearance	= and creepaoุ	ge distance	e measure	ments			
Clearance (cl) and creepage distance (cr) at/of/between:	U peak (V)	U r.m.s. (V)	Requi		cl (mm)	Required cr (mm)	cr (mm)
Functional:		1				1	Т
Basic / supplementary:]
Bacio / cappiomoniary.	T						T
							1
Reinforced:				'			

Supplementary information:

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 91 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

2.10.5	TABLE: D	istance thr	ough insulatio	n measure	ements				
Distance th	nrough insu	lation (DTI)) at/of:	U peak (V)	U r.m.s (V)	s. Te volta (V	ige	equired DTI (mm)	DTI (mm)
Basic:									
Supplemer	ntary:			<u> </u>					
Reinforced	:								
Supplemen	ntary inform	nation:							
4.3.8	TABLE: E	Batteries							
The tests of data is not		applicable	only when ap	propriate b	attery				
Is it possib	le to install	the battery	in a reverse p	oolarity pos	sition?				
	Non-re	chargeable	I			Rechargeable batteries			
		arging	Un- intentional	Charging		Discharging			d charging
	Meas. current	Manuf. Specs.	charging	Meas. current	Manuf. Specs.	Meas. current	Manuf. Specs.		Manuf. Specs.
Max. current during normal condition									
Max. current during fault condition									
-									
Test results									Verdict
- Explosion		erv							
		,							

Supplementary information:

- Emission of flame or expulsion of molten metal

- Electric strength tests of equipment after completion of tests

Report No. xxxxxx IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 / Page 92 of 95

Dated: xxxxxx IEC 60950-1: 2005 + A1:2009 + A2 : 2013

4.5	TABLE: Temperature rise measurements										
as for power Temperature	s were measured input measureme s are calculated of°C(T	ents of table 1 according cl.	.6.2 res 1.4.12.3	ulted with r	in high egard	est tem to the r	nperature	values.		•	ition
test voltage(s) (V):			A:	V,	Hz		B:	V, Hz		
t _{amb1} (°C):	A:	B:		t _{amb2}	(°C):			A:	B:		
Temperature of part/at: (measured with thermocouples)			Measured temperature rise at T _{amb}			at tem	Calculated temperature at T _{ma}			wed (°C)	
	A B A B T (°C)										
Supplementa	ary information:										
	s measured with	winding resis	tance m	ethod	: Not	used					
	T of winding: stance method)	(V)	R ₁ (<u>s</u>	Ω)	R ₂	(Ω)	T (°C)		allowed 「 _{max} (∘C)		ation ass
Supplementa	ary information:										
	TABLE: Ball pre				-						
	Allowed impress	sion diameter	(mm)		:	≤ 2 mı					_
Part								ion diameter mm)			
Supplementa	ary information:										

Report No. xxx	XXX	IS 13252	(Part 1): 201	0 + A1: 2	013 + A2 : 20)15 /	Pag	ge 93 of 95	
Dated: xxxxxx		IEC 60	950-1: 2005	+ A1:200)9 + A2 : 201	3			
4.6.1, 4.6.2 Tal	ble: Enclosure	opening me	easurements						
Location	ocation			(Comments				
Supplementary	information:								
4.7 Tal	ble: Resistanc	e to fire							
Part			Type of r	material			Flammability		
	- 111	aterial			(111111)	(mm) class			
Supplementary	information:								
Supplementary	miorination.								
5.1.6 TA	RI E: Touch a	urrent and n	rotoctivo con	ductor our	ront mossura	mont			
	BLE: Touch co st voltage (V).				V,I				
				<u> </u>	·				
Measurement location F			Polarity (normal) P [mA]		y (reverse) [mA]	Limit Comn (mA)		nents	
(Terminal A connected to)		Switch: ON	Switch: OFF	Switch:	Switch: OFF				
Earth terminal ("e" = open)									
Operating Pane ("e" = close)	·l								
Supplementary	information:	'	· · · · · · · · · · · · · · · · · · ·		·	•	•		
5.2 TA	BLE: Electric	strength tes	ts, impulse to	ests and v	voltage surge	tests			
Test voltage ap	st voltage applied between:			(A	age shape AC, DC, Ise, surge)	Test voltage (V)		Breakdown Yes / No	
Functional:									
Basic / supplem	entary:			<u> </u>	I				
Reinforced:				1	<u> </u>				
Supplementary	information:			<u> </u>	l		I		

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 94 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

5.3	TABLE: Fault condition tests							
	Ambient temperature (°C)						_	
	Power source for E output rating							_
Componer No.	nt Fault	Supply voltage (V)	Test time	Fuse #	Fuse curren (A)	Observa		
Supplement	tary information:							
	T							
C.2	TABLE: Insulation	of transforn	ners					
	Transformer part n	ame		:				_
	Manufacturer			:				_
	Туре			:				
	cl) and creepage) at/of/between:	U peak (V)	U r.m.s (V)		uired mm)	cl (mm)	Required cr (mm)	cr (mm)
	ut winding and output winding							
Primary/inpu (internal)	ut winding and core							
Secondary/c	output winding and							
Primary/inpu secondary/o (external)								
Primary/input part and core (external)								
Primary/input part and secondary/output winding (external)								
Secondary/output part and core (external)								
Secondary/o primary/inpu (external)	output part and it winding							
Description	of design:							
(a) Bobbin								
Primary/inp	ut pins		:					
Secondary/o	output pins		:					
Material (ma	anufacturer, type, ra	tings)	:					
Thickness (mm)		:					

Report No. xxxxxx	IS 13252 (Part 1): 2010 + A1: 2013 + A2 : 2015 /	Page 95 of 95
Dated: xxxxxx	IEC 60950-1: 2005 + A1:2009 + A2 : 2013	

(b) General
Please insert here a description of the transformer design describing:
Supplementary information: