# BUREAU OF INDIAN STANDARDS

**For immediate release**

**Press Note No: PRD/Press Note/8/2017-18** **25th August 2017**

## BIS raids fire extinguisher manufacturing unit

Bureau of Indian Standards (BIS) conducted enforcement raid at M/S Palladium Safety Solutions Pvt. Ltd. In New Delhi recently. The firm was manufacturing portable fire extinguisher having BIS mark under brand name " Palex" without having valid BIS licence, violating Section 11 (1) of BIS Act, 1986 under which there is a provision of fine of Rs. 50,000/- and/or one year imprisonment.

Alka
Deputy Director, PR
23234048

# भारतीय मानक ब्यूरो

प्रेस नोट सं: पीआरडी/प्रेस नोट/8/2017-18 25.08.2017

## भारतीय मानक ब्यूरो का फायर एक्सटिंगिवशर यूनिट पर छापा

भारतीय मानक ब्यूरो (भामाब्यूरो) ने हाल ही में नई दिल्ली में मैसर्स पैलेडियम सेफ्टी सोल्यूश्नस प्राइवेट लिमिटेड पर प्रवर्तन संबंधी छापा मारा। यह इकाई भामाब्यूरो का वैध लाइसेंस लिए बिना "पैलेक्स" ब्रांड नाम के अंतर्गत फायर एक्सटिंगिवशर का निर्माण कर रही थी, जो भामाब्यूरो अधिनियम 1986 की धारा 11(1) का उल्लंघन है। भामाब्यूरो अधिनियम के अनुसार भामाब्यूरो से लाइसेंस लिए बिना मुहर का उपयोग या इसकी नकल दंडनीय अपराध है, जिसके लिए 50,000/- रुपए का जुर्माना अथवा/और एक वर्ष की सजा हो सकती है।

अलका
उपनिदेशक जनसंपर्क
23234048

CARBON DIOXIDE

Palex™

MAKE IN INDIA

CARBON DIOXIDE

KEEP THIS END UP WHILE USING

KEEP THIS END UP WHILE USING

STORED PRESSURE TYPE MULTIPURPOSE FIRE EXTINGUISHER

SUITABLE FOR CLASSES OF FIRE

B — PETROL, OIL, PAINTS, CHEMICALS

C — LPG, GAS, ELECTRICALLY STARTED FIRES

**MAINTENANCE**

Care and Maintenance as per IS 2190 : 2010. Inspect periodically and ensure that there is no pressure drop. Lock Pin and Tamper Seal must be intact

**PRECAUTION**

Contents under pressure. Do not temper with the shell. Break the Safety Seal only in case of fire. Do not relay on partially used or discharge extinguisher.

**INSPECTION**

Tamper Seal and Tamper Indicator are not broken or missing. It is full (by weighing or lifting) It is not obviously damage, Corroded, Leaking or has Clogged Nozzle. Its Pressure Gauge reading and Indicator is in the operatable range or position.

**RECORDS**

Record Maintenance data and Recharge Dates on attached tag.

**CAUTION**

Do not rely on partially use / discharged fire extinguisher

Fire Rating : 21B

Service Pressure : 15 Bar

Operating Temp : -10° To +55°C

IS : 15683

CM/L : 2741456

JAS-ANZ

ISO 9001:2008

CE

CERTIFIED

**MODE OF OPERATION**

1. Check the pressure gauge needle in the green zone

2. Hold upright pull pin squeeze lever

3. Direct discharge at the base of flame with rapid sweeping motion

Tested at : 35kgf/cm²

Batch No. : 170801

Content : CARBON DIOXIDE

SR. NO. 74

GROSS WT. 3.4 ±2%

CAPACITY 2 Kg

YEAR OF MFG. 2017

Palex™

Marketed By:

Palladium Safety Solutions Private Limited

Manufactured by : Chirag Industries (An ISO 9001:2008 Certified Co.)