

PRODUCT MANUAL FOR NON-FERROUS METAL SLIDING DOOR BOLTS (ALDROPS) FOR USE WITH PADLOCKS ACCORDING TO IS 2681: 1993

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure coherence of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification licence/certificate.

1.	Product	:	IS 2681: 1993					
	Title		NON-FERROUS METAL SLIDING DOOR BOLTS (ALDROPS) FOR USE WITH PADLOCKS					
	No. of Amendments	:	2					
2.	Sampling Guidelines:							
a)	Raw material	:	As per Cl.5 of IS 2681: 1993					
b)	Grouping guidelines	:	Please refer ANNEX – <u>A</u>					
c)	Sample Size	:	5 nos of door bolts					
3.	List of Test Equipment	:	Please refer ANNEX – B					
4.	Scheme of Inspection and Testing	:	Please refer ANNEX – <u>C</u>					
5.	Possible tests in a day	:	All tests					
6.	Scope of the Licence:							
	"Licence is granted to use Standard Mark as per IS 2681: 1993 with the following scope:							
	Name of the product	Non-ferrous metal Sliding door bolts (aldrops) for use with padlocks						
	Type	Type 1, 2, 3						
	Size							
	Material							

BUREAU OF INDIAN STANDARDS

Manak Bhawan, 9, Bahadur Shah Zafar Marg,

New Delhi – 110002

ANNEX A

Grouping Guidelines

1. Non-ferrous metal sliding door bolts as per IS 2681 are classified based on the following:

Type	Material	Size			
Type 1	Brass	150 mm, 200 mm, 250 mm, 300mm, 375 mm and 450 mm			
Type 2	Diuss				
Type 3	Aluminium Alloy	200 mm, 250 mm, 300mm,350 mm, 375 mm and 450 mm			

- 2. Considering the above, one sample each of the smallest and highest size from each type of door bolt shall be tested to cover all sizes in that size-range for that particular type of door bolt.
- 3. Separate samples of door bolt of each material (Brass/Aluminium alloy) shall be tested to cover that material in the scope of the licence.
- 4. The Firm shall declare the varieties of various Door Bolts they intend to cover in the Licence. The Scope of Licence may be restricted based on the manufacturing and testing capabilities of the manufacturer.
- 5. During operation of the licence, BO shall ensure that all the varieties covered in the licence are tested in rotation to the extent possible.

ANNEX B

List of Test Equipment

Major test equipment required to test as per the Indian Standard

Sl. No.	Tests used in with Clause	Test Equipment			
	Reference				
1.	Dimensions and Tolerances	a) Vernier Calliper			
	(Clause 6, Table 2 and 3,	b) Micrometre			
	Fig.1)	c) Countersunk head of Wood Screws as per IS 6760			
	M (C1 7)				
2.	Manufacture (Clause 7)	a) Vernier Calliper			
		b) Countersunk head of Wood Screws as per IS 6760			
3.	Finish (Clause 8)	Anodizing coating thickness gauge			
		Or			
		Test equipment, chemicals as per IS 1868			

The above list is indicative only and may not be treated as exhaustive.

ANNEX C

Scheme of Inspection And Testing

- **1. LABORATORY** A laboratory shall be maintained which shall be suitably equipped (as per the requirement given in column 2 of Table 1) and staffed, where different tests given in the specification shall be carried out in accordance with the methods given in the specification.
- **1.1** The manufacturer shall prepare a calibration plan for the test equipments.
- **2. TEST RECORDS** The manufacturer shall maintain test records for the tests carried out to establish conformity.
- **3. LABELLING AND MARKING** As per the requirement of IS 2681:1993.
- 3.1 **PACKING** Packing of door bolts shall be done as per clause 10 of IS 2681:1993.
- **4. LEVELS OF CONTROL** The tests as indicated in column 1 of Table 1 and the levels of control in column 3 of Table 1, shall be carried out on the whole production of the factory which is covered by this plan and appropriate records maintained in accordance with paragraph 2 above.
- **4.1** All the production which conforms to the Indian Standards and covered by the licence should be marked with Standard Mark.
- **5. REJECTIONS** Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

TABLE 1

(1)			(2)				
Test Details				Test equipment Levels of Control			evels of Control
Cl.	Requirement	Test Method		requirement	No. of	Frequency	Remarks
		Clause	Reference	R: required (or)	Sample		
				S: Sub-contracting permitted			
5	Material	Cl. 5	IS 2681	S	One	Each consignment	No further testing is required if accompanied with test certificate or ISI marked.
6	Dimensions & tolerances	Cl. 6, Table 2, Table 3	IS 2681	R	5	Each type and size from every hour production	In case of failure of any sample, entire production during the hour shall be checked for dimensions and only those door bolts, which are passing, shall be marked.
7	Manufacture	Cl.7.1, 7.2	IS 2681	-	-	Each door bolt	-
8	Finish (Visual)	Cl.8.1	IS 2681	-	-	Each door bolt	-
	Anodizing (for aluminium alloy door bolts)	C1.8.2	IS 2681	R	3	From aluminium anodizing	alloy anodized in a shift of production of

Note-1: Sub-contracting is permitted to a laboratory recognized by the Bureau or Government laboratories empanelled by the Bureau.

Note-2: Levels of control given in column 3 are only recommendatory in nature. The manufacturer may define the control unit/batch/lot and submit his own levels of control in column 3 with proper justification for approval by BO Head.