

#### उत्पाद मानुयल पशुओ के लिए मिश्रित आहार IS 2052 : 2029 के अनुसार

## PRODUCT MANUAL FOR COMPOUNDED FEEDS FOR CATTLE ACCORDING TO IS 2052: 2009

भारतीय मानक ब्यूरो (अनुरूपता मूल्यांकन) विनियम की स्कीम-I के तहत यह उत्पाद मानुयल प्रमाणीकरण के प्रचलन मे रीति और पारदर्शिता के सुसंगता सुनिश्चित करने के लिए सभी क्षेत्रीय/शाखा कार्यालयों एवं लाइसेन्स धारियों द्वारा संदर्भ सामग्री के रूप मे उपयोग किया जाएगा। बीआईएस लाइसेन्स/प्रमाण पत्र प्राप्त करने के इच्छुक भावी आवेदकों द्वारा भी इस दस्तावेज़ का उपयोग किया जा सकता है।

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure coherence of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification licence/certificate.

1.	उत्पाद Product	:	IS 2052 : 2009		
	शीर्षक Title	:	पशुओं के लिए मिश्रित आहार Compounded Feeds for Cattle		
	संशोधन संख्या No. of Amendments	:	04		
2.	नमुनाकरण दिशा निर्देश Sampling Guidelines:				
a)	कच्चा माल Raw material		-For compliance to clause 4.2.2 (regarding proportion of urea, when incorporated and percent of easily digestible carbohydrates) and clause 4.2.3, declaration shall be obtained from the manufacturerMaterial of plant origin used for manufacture of Compounded Feeds for Cattle shall conform to clause 4.2.4 (see also cl 6 of SIT).		
b)	समूहिकरण दिशा निर्देश Grouping Guidelines	:	NA		
c)	नमूने का परिमाण Sample Size	:	500g		
3.	परीक्षण उपकरणो की सूची List of Test Equipment	:	कृपया Annex-A देखें Please refer ANNEX <u>A</u>		
4.	निरीक्षण व परीक्षण स्कीम Scheme of Inspection and Testing	:	कृपया Annex-B देखें Please refer ANNEX <u>B</u>		

5.	एक दिन में संभावित परीक्षण						
٥.	Possible tests in a day:						
	i. Description						
	ii. Moisture						
	iii. Crude Protein						
	iv. Acid-insoluble ash.						
6.	लाइसेन्स का कार्यक्षेत्र/Scope of the Licence :						
	ıs 2052 : 2009 के अनुसार मानक मुहर का उपयोग करने के लिए लाइसेन्स निम्नलिखित कार्यक्षेत्र के लिए प्रदान किया जाता है						
	Licence is granted for use of the Standard Mark as per IS 2052 : 2009 with the						
	following scope:						
	उत्पाद का नाम	Company ded Frede for Coulo					
	Name of the product	Compounded Feeds for Cattle					
	Type	-Type I					
	Type	-Type II					

BUREAU OF INDIAN STANDARDS Manak Bhawan, 9, Bahadur Shah Zafar Marg, New Delhi – 110002

# ANNEX – A TO PRODUCT MANUAL FOR COMPOUNDED FEEDS FOR CATTLE ACCORDING TO IS 2052 : 2009

#### LIST OF TEST EQUIPMENTS

Major test equipment required to test as per requirements of Indian Standard.

S. No.	Test Equipment	Tests used in with Clause Reference
1	Colodia di consulta di consult	
1.	Grinding arrangement to grind sample,	Preparation of test
	1.00 mm IS sieve or ASTM sieve 18 or BS sieve 16	sample
	or Tyler sieve 16,	
	Well stoppered glass bottle	3.6
2	Weighing balance, LC 1 g	Moisture
	Aluminium dish with cover, at least 50 mm diameter	Cl 4.3 & 7.1, Table 1
	and about 40 mm depth	
	Air oven, LC 2 <sup>o</sup> C, Desiccator.	
2	Kjeldhal flask, 500 ml capacity	Crude protein
	Distillation assembly	Cl 4.3 & 7.1, Table 1
	Potassium Sulphate or anhydrous Sodium Sulphate,	and
	Copper Sulphate, Conc. Sulphuric Acid, Sodium	Total Nitrogen
	Hydroxide, Standard Sulphuric acid, Standard	Cl 4.2.2
	Sodium Hydroxide solution, Methyl Red Indicator,	
	Boric Acid,	
	Magnesium Oxide. Weighing balance, round bottom	
	flask, burette.	
3	Air oven, LC 2 <sup>0</sup> C	Crude fat
	Weighing balance, LC 0.5 g	Cl 4.3 & 7.1, Table 1
	Soxhlet apparatus	
	Steam bath	
	Desiccator	
	Petroleum ether in the boiling range of 40°C to 60°C	
	Hexane, food grade conforming to IS 3470	
4	Weighing balance, LC 1 g	Crude fibre
	Soxhlet apparatus	Cl 4.3 & 7.1, Table 1
	Petroleum ether in the boiling range of 40°C to 60°C	
	Hexane, food grade, One litre conical flask, Beaker,	
	Dilute Sulphuric Acid, Sodium hydroxide solution,	
	Hot plate	
	Reflux water condenser, Fine linen filter	
	Funnel, Litmus paper, Sodium Hydroxide	
	Gooch crucible, Ethyl alcohol, air oven LC 1 <sup>o</sup> C, Thin	
	but compact layer of ignited asbestos, Muffle furnace	

5	Weighing balance, LC 1 mg	Acid-insoluble ash
	Porcelain, silica or platinum dish	Cl 4.3 & 7.1, Table 1
	Meker burner, Muffle furnace, Electric air oven, LC	
	2 <sup>0</sup> C, Dilute Hydrochloric acid	
	Watch glass, Water bath, Whatman filter paper no. 42	
	or equivalent, Silver Nitrate,	
	Desiccator	
6	Weighing balance, LC 1 g	Urea
	Kjeldhal flask, 500 ml capacity	Cl 4.3 & 7.1, Table 1
	Distillation assembly with round bottom flask of	·
	1000 ml capacity	
	Conical flask of 500 ml, Methyl Red indicator,	
	Diglycol Stearate, Benzene	
	Alcohol, Dubutyl Phthalate, Urease	
	Hydrochloric acid, Calcium Chloride	
	Sulphuric acid, Sodium Hydroxide	
	Magnesium Oxide	
7	Magnetic stirrer, Spectrophotometer, Measuring	Total sulphur
	spoon (0.2 to 0.3 ml), Volumetric flasks, 250 ml	Cl 4.2.2
	flasks, Stirring bars, Glyserol, Conc. Hydrochloric	
	acid, Distilled water, Ethyl alcohol, Sodium chloride,	
	Barium Chloride, Standard Sulphur solution,	
	Potassium sulphate, Analytical balance, Measuring	
	jar.	
8	Kjaldahl flask, Atomic Absorption Spectrophotometer,	Cadmium
	Hydride Generation Vessel Accessory, Potentiometric	Cl 4.3 & 7.1 and Table 1
	Recorder, Nitric Acid, Perchloric Acid, Sulphuric Acid	(Cl 15 of IS 1699)
	Hydrochloric Acid, Metal Free Water, Sodium Sulphate	
	Sodium Borohydride Pellets, Potassium Chloride Standard Cadmium Solution.	
	Standard Cadimidin Solution.	

The list above is indicative only and may not be taken as exhaustive.

## ANNEX-B SCHEME OF INSPECTION AND TESTING

### FOR COMPOUNDED FEEDS FOR CATTLE ACCORDING TO IS 2052: 2009

- **1.LABORATORY** A laboratory shall be maintained which shall be suitably equipped (as per the requirement given in column 2 of Table 1) and staffed, where different tests given in the specification shall be carried out in accordance with the methods given in the specification.
- **1.1** The manufacturer shall prepare a calibration plan for the test equipments.
- **2. TEST RECORDS** –The manufacturer shall maintain test records for the tests carried out to establish conformity.
- **3. PACKING AND MARKING** The Standard Mark, as given in the Schedule of the licence, shall be stencilled/printed on each bag of Compounded Feeds for Cattle or printed on the label applied to it, as the case may be, provided always that the material in each bag to which this mark is thus applied, conform to every requirement of the specification.
- **3.1 Marking** Each bag shall be legibly marked or labelled to give the information as per clause 5.2 of IS 2052. In addition, the following details shall be mentioned on each container legibly and indelibly:

a) BIS	Licence No. CM/L				
b) BIS	website details i.e -"I	For details of BIS	certification	please visit	www.bis.gov.in'

- **3.2 Packing** Compounded cattle feeds shall be packed in clean and sound plain or polyethylene lined jute or laminated paper bags. The mouth of each bag shall be machine stitched.
- **4. CONTROL UNIT** –For the purpose of this Scheme, the entire quantity of material manufactured continuously in a day shall constitute a control unit.
- **5. LEVELS OF CONTROL** The tests as indicated in column 1 of Table 1 and the levels of control in column 3 of Table 1, shall be carried out on the whole production of the factory which is covered by this plan and appropriate records maintained in accordance with paragraph 2.0 above.
- 5.1 All the production which conforms to the Indian Standards and covered by the licence should be marked with Standard Mark.
- 5.2 On the basis of the test results, decision, regarding conformity or otherwise of a control unit shall be made as follows:
- 5.2.1 Three Samples shall be taken from each control unit as per Table-1 at equal intervals at the time of filling of bags. These samples shall be tested separately for crude protein and all the samples shall pass.
- 5.2.2 A composite sample shall be prepared by mixing equal proportion from the three samples drawn under 5.2.1 and tested for all the requirements (except crude protein).

5.2.3 The control unit shall be accepted as conforming to the requirements of the specification if all the individual samples meet the crude protein requirement and the composite sample passes in the relevant requirements. If the sample fails to meet one or more of the requirements the control unit shall not be marked. However, the material may be suitably reprocessed and the defect(s) rectified. Such reprocessed material when tested again as per clause 5.2.1, 5.2.2 above, shall conform to all the requirements of the specification, before it is marked.

In case of failure of samples in Sl. No. 8 to 11 & 13 to 17 (of Table 1 to SIT), samples from first two batches manufactured after taking corrective actions shall be tested for the next three months and in case all are passing, original frequency shall be restored.

- **6. RAW MATERIAL** Besides common salt, mineral mixture (Type II), Dicalcium Phosphate (DCP), Calcite powder and vitamin A, any of the ingredients listed in Annex B may be used for compounded cattle feeds. For proportion of urea and percent of easily digestible carbohydrates, when urea is incorporated shall be as per clause 4.2.2 of IS 2052 and for compliance to clause 4.2.3, declaration shall be obtained from the manufacturer. Material of plant origin used for manufacture of Compounded Feeds for Cattle shall conform to clause 4.2.4, alternatively, test certificate from supplier may be accepted.
- **7. REJECTIONS**—Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

#### TABLE 1 LEVELS OF CONTROL

		(1)			(2)	(3)		
		Test Details			Test equipment	Recommended Levels of Control		
	Cl.	Requirement	Test	Test Method IS	requirement	No. of	Frequency	Remarks
S.No.			Method		R: required (or)S:	Sample		
			Cl. Ref.		<b>Sub-contracting</b>			
					permitted			
1.	4.1	Description	4.1	IS 2052		-	-	Entire material shall
					R			conform.
2.	4.2	Ingredients	4.2.1	-do-			Each	Records to be maintained
					-	-	consignment	indicating the test results,
								the quantity added, etc.
	4.2.2	Total Nitrogen	5	IS 7874 (Pt 1)	R	-do-	-do-	To be tested when urea is
					K			added
	4.2.2	Sulphur	Annex B	IS 1664	R	-do-	-do-	-do-
	4.2.4	Aflatoxin B <sub>1</sub> in	-	IS 13427		-do-	-do-	Alternatively, TC from
		materials of plant origin	Annex G	IS 2052	S			supplier may be accepted.
3.	4.3 & 7.1,	Moisture	4	IS 7874 (Pt 1)		One	Each control	Composite sample from
	Table 1			, ,	R		unit	three samples
4.	-do-	Crude protein	5	-do-	R	Three	-do-	See cl. 5.2.1 of SIT
5.	-do-	Crude fat	7	-do-	R	One	-do-	Composite sample from
								three samples
6.	-do-	Crude fibre	8	-do-	R	-do-	-do-	-do-
7.	-do-	Acid-insoluble ash	10	-do-	R	-do-	-do-	-do-
8.	4.3 & 7.1,	Salt	4	IS 7874 (Pt 2)	C	-do-	Once in a	Composite sample from
	Table 1				S		month	three samples
9.	-do-	Calcium	-	IS 13433 (Pt 1/Pt 2)	S	-do-	-do-	-do-

10.	-do-	Total Phosphorus	6	IS 7874 (Pt 2)	S	-do-	-do-	-do-
				or IS 14828	ာ			
11.	-do-	Available	Annex C	IS 1374	S	-do-	-do-	-do-
		Phosphorus			ာ			
12.	-do-	Urea	-	IS 7874 (Pt 1)	R	-do-	Each control	-do-
					K		unit	
13.	-do-	Vitamin A	-	IS 15120	S	-do-	Once in a	-do-
					S		month	
14.	-do-	Vitamin D	Annex E	IS 2052	S	-do-	-do-	-do-
15.	-do-	Vitamin E	Annex F	-do-	S	-do-	-do-	-do-
16.	-do-	Aflatoxin B <sub>1</sub>	Annex G	IS 13427	S	-do-	-do-	-do-
17.	-do-	Cadmium	15	IS 1699	S	-do-	-do-	-do-

Note-1: Whether test equipment is required or sub-contracting is permitted in column 2 shall be decided by the Bureau and shall be mandatory. Sub-contracting is permitted to a laboratory recognized by the Bureau or Government laboratories empanelled by the Bureau.

Note-2: Levels of control given in column 3 are only recommendatory in nature. The manufacturer may define the control unit/batch/lot and submit his own levels of control in column 3 with proper justification for approval by BO Head.