



उत्पाद मैनुअल

आई एस 7285 (Part 2): 2017 के अनुसार

फिर से भरे जा सकने वाले निर्बाध इस्पात के गैस सिलेंडर्स- 1100 एम पी ए (112 केजीएफ/वर्ग एमएम) से कम की तन्यता वाले इस्पात के क्वेंचड एवं टैंपर सिलिन्डर के लिए

दस्तावेज संख्या-पी एम/आई एस 7285 (Part 2)/2/ जुलाई 2021

भारतीय मानक ब्यूरो की स्कीम-I (अनुरूपता मूल्यांकन) विनियम, 2018 के तहत यह उत्पाद मैनुअल प्रमाणीकरण के प्रचालन में रीति और पारिश्रिता की सुसंगतता सुनिश्चित करने के लिए सभी क्षेत्रीय/शाखा कार्यालयों और लाइसेंसि द्वारा संदर्भ सामग्री के रूप में उपयोग किया जाएगा। बीआईएस प्रमाणीकरण लाइसेंस/ प्रमाणपत्र प्राप्त करने के इच्छुक भावी आवेदकों द्वारा भी इस दस्तावेज का उपयोग किया जा सकता है।

PRODUCT MANUAL FOR REFILLABLE SEAMLESS STEEL GAS CYLINDERS - QUENCHED AND TEMPERED STEEL CYLINDERS WITH TENSILE STRENGTH LESS THAN 1 100 MPa (112 kgf/mm²) ACCORDING to IS 7285 (Part 2):2017

Document No.-PM/IS 7285 (Part 2)/2/ July 2021

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure coherence of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification licence/certificate.

भारतीय मानक ब्यूरो
BUREAU OF INDIAN STANDARDS
मानक भवन, ९, बहादुर शाह ज़फ़र मार्ग
Manak Bhawan, 9, Bahadur Shah Zafar Marg
नई दिल्ली- ११०००२
New Delhi – 110002



**PRODUCT MANUAL FOR
REFILLABLE SEAMLESS STEEL GAS CYLINDERS -
QUENCHED AND TEMPERED STEEL CYLINDERS WITH
TENSILE STRENGTH LESS THAN 1 100 MPa (112 kgf/mm²)
ACCORDING TO IS 7285 (Part 2):2017**

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure coherence of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification licence/certificate.

| | | | |
|----|---|---|--|
| 1. | Product | : | IS 7285 (Part 2):2017 |
| | Title | : | Refillable Seamless Steel Gas Cylinders - Quenched and Tempered Steel Cylinders with Tensile Strength less than 1100 MPa (112 kgf/mm ²) |
| | No. of amendments | : | One |
| 2. | Sampling Guidelines | | |
| a) | Raw material | : | Steel - Clause 5 of IS 7285 (Part 2) |
| b) | Grouping Guidelines | : | Each new design of cylinder shall be tested for all requirements for considering GoL/ CSoL. New design of cylinder is defined at Clause 9.1 of IS 7285 (Part 2): 2017. |
| c) | Sample Size | : | Please refer Annex - A |
| 3. | List of Test Equipment | : | Please refer Annex - B |
| 4. | Scheme of Inspection and Testing | : | Please refer Annex - C |
| 5. | Possible tests in a day | : | Please refer Annex - D |
| | | | |
| 6. | Scope of the Licence | : | Please refer Annex - E |

BUREAU OF INDIAN STANDARDS
Manak Bhawan, 9, Bahadur Shah Zafar Marg,
New Delhi – 110002

ANNEX A**Sample Size**

For considering GoL/CSoL, a trial batch of prototype Cylinders as per the approved drawings shall be manufactured during the joint inspection of BIS and Statutory Authority after in-principle approval is received from the statutory authority. Unless otherwise stated by the statutory authority, the trial batch shall be of minimum 50 prototype containers. Following samples sample shall be drawn for factory testing and independent testing:

Samples for Type approval (Type tests): As per Cl. 9.2 of IS 7285 (Part 2)

Note: Currently being done in Factory in view of partial test facilities at BIS/OSLs.

Samples for Independent Tests (IT Samples):

| Sl. No. | Description of test | Clause reference | No. of samples |
|---------|----------------------------------|----------------------|------------------|
| 1. | Mechanical Test | 10.1.3 (a), (b), (c) | As per Cl. 9.2.2 |
| 2. | Water capacity | 7.11 | One |
| 3. | Test piece for chemical analysis | 5 | Five pieces |

ANNEX B**List Of Test Equipment***Major test equipment required to test as per the Indian Standard*

| Sl. No. | Tests used in with Clause Reference | | Test Equipment |
|---------|-------------------------------------|--------------|--|
| | Test | Clause No. | |
| 1 | Depth of Concave bottom | Clause 6.4 | Depth Gauge |
| 2 | Neck threads | Clause 6.8 | Thread inspection gauges |
| 3 | Valve Fitting | Clause 6.6.3 | Torque Wrench |
| 4 | Wall Thickness | Clause 7.2 | Ultrasonic Thickness Gauge |
| 5 | Surface Defects | Clause 7.3 | Ultrasonic Thickness Gauge |
| 6 | Out Of Roundness | Clause 7.5 | Vernier Calliper or Outside Micrometre or Set of Outside Calliper and Steel Rule |
| 7 | Mean Diameter | Clause 7.6 | Pi tape |
| | | | Outside Calliper with Steel Rule |
| | | | Micrometre |
| 8 | Straightness | Clause 7.7 | Feeler Gauge |
| | | | Steel Rule/Straight Edge |
| | | | Steel Rule/Straight Edge |
| 9 | Verticality | Clause 7.8 | Fixture for measuring Verticality |
| | | | Feeler Gauge |
| | | | Steel Rule/Straight Edge |
| 10 | Stability | Clause 7.9 | Vernier Calliper |
| | | | Scale |
| 11 | Water Capacity | Clause 7.11 | Digital Electronic Balance |
| 12 | Hydraulic Bursting Test | Clause 10.5 | Pressure Gauge |
| | | | Test Fluid Reservoir |
| | | | Tank for measurement of fluids |
| | | | Pressure/Time curve recorder |
| | | | Vent or air release valve |
| | | | Test well |
| | | | High Pressure Pump |
| 13 | Pressure cycling Test | Clause 9.2.3 | Pressure Gauge |
| | | | Temperature Sensor |
| | | | Non-Corrosive Liquid |
| | | | Pressure cycling test set up |
| | | | Stop Watch |
| 14 | Base Check | Clause 9.2.4 | Magnifying Glass |
| 15 | Tensile Test | Clause 10.2 | Universal Testing Machine |
| | | | Vernier Calliper |
| | | | Micrometre |

| | | | |
|----|--|------------------------------------|--|
| 16 | Impact Test | Clause 10.3 | Impact testing Machine |
| | | | Deep Freezer/Dry ice |
| | | | Thermometer– Digital / Glass type |
| | | | Profile Projector/Go-No Go gauges |
| 17 | Bend Test | Clause 10.4 | Universal Testing Machine |
| 18 | Hydrostatic Stretch Test | Clause 11.2 Water Jacket Method | Overflow |
| | | | Hydraulic Line Valve |
| | | | Water Supply |
| | | | Jacket Filling Valve |
| | | | Air Bleed Valve |
| | | | Pump |
| | | | Relief device |
| | | | Drain |
| | | | Calibrated Burette |
| | | | Priming Valve |
| | | | Pressure Gauge |
| | | | Weighing Balance – Electronic |
| | | Non- Water Jacket Method | Water Tank |
| | | | Bleed Valve |
| | | | Pressure Gauge |
| | | | Pump |
| | | | Weighing Balance Electronic |
| 19 | Hardness test | Clause 11.3 | Hardness Testing Machine (Brinell or Rockwell) |
| 20 | Leakage Test | Clause 11.4 | Pressure Gauge |
| | | | Tank with Lighting Arrangement |
| 21 | Colour Identification | Clause 12 | Coating thickness Gauge |
| 22 | Sulphide Stress Cracking Resistance Test | Clause 9.2.5 | Universal testing machine |
| | | | Distilled Water |
| | | | Sodium Acetate tri-hydrate |
| | | | Acetic Acid |
| 23 | Ultrasonic Examination | Clause 7.4 | Ultrasonic Testing Machine |
| | | | Standard Piece for UT |
| | | | Ultrasonic Flaw Detector |

The above list is indicative only and may not be treated as exhaustive.

ANNEX C

Scheme Of Inspection And Testing

1. LABORATORY - A laboratory shall be maintained which shall be suitably equipped (as per the requirement given in column 2 of Table 1) and staffed, where different tests given in the specification shall be carried out in accordance with the methods given in the specification.

1.1 The manufacturer shall prepare a calibration plan for the test equipments. The following equipments shall be calibrated at a frequency shown against each and records kept:

1.1.1 Tensile Testing Machine - Once in a year

1.1.2 Impact Testing Machine - Once in a year

1.1.3 Pressure Gauges - At least once in a month

1.1.4 Pyrometer used for heat treatment furnace - Once in six months

2. TEST RECORDS – The manufacturer shall maintain test records for the tests carried out to establish conformity. Records of all the tests made at the cylinder manufacturer's work shall be kept for the life time of the cylinder and copies of test certificates shall be forwarded to the purchaser of the cylinder and the inspecting authority.

3. LABELLING AND MARKING - As per the requirements of IS 7285 (Part 2):2017.

4. BATCH - For the purpose of this scheme, a quantity of upto 200 cylinders plus cylinders for destructive testing, of the same nominal diameter, thickness and design, made successively from the same heat number of steel and subjected to the same heat treatment for the same duration of time shall constitute a Batch.

4.1 The identity of each batch shall be maintained. Each batch conforming to all the requirements shall be accompanied by a Certificate in accordance with clause 13 of IS 7285 (Part 2).

5. LEVELS OF CONTROL - The tests as indicated in column 1 of [Table 1](#) and the levels of control in column 3 of [Table 1](#), shall be carried out on the whole production of the factory which is covered by this plan and appropriate records maintained in accordance with paragraph 2 above.

6. HEAT TREATMENT - The heat treatment of cylinders shall be done as per clause 5.5 of IS 7285 (Part 2). The cylinders shall be punched with serial number before heat treatment to maintain traceability throughout the manufacturing process.

6.1 Adequate care shall be taken to ensure the consistency of heat treatment cycle. The deviation of temperature shall be within the specified temperature range. In case the temperature goes outside the specified limits, furnace shall be stopped and all such cylinders shall be segregated. Heat treatment shall be resumed only after attaining the requisite temperature and the furnace temperature is maintained between the specified limits. The complete records of heat treatment cycle and interruptions of cycle shall be maintained.

7. INSPECTION AND TESTING/ RE-TESTS

7.1 In order to ensure that the cylinders are in compliance with IS 7285 (Part 2), they shall be subjected to Inspection and Testing in accordance with clause 8 of IS 7285 (Part 2).

7.2 In the event of failure of cylinders in meeting the requirements, procedure in accordance with clause 7.10.1 of IS 7285 (Part 2) shall be followed for retesting/re-heat treatment.

8. REJECTIONS – Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

TABLE 1

| (1) | | | | (2) | (3) | | |
|--------------|--------------------------------------|-------------------------------------|------------------|--|-------------------|------------------|---|
| Test Details | | | | Test equipment requirement R: required (or) S: Sub-contracting permitted | Levels of Control | | |
| Cl. | Requirement | Test Methods | | | No. of Sample | Frequency | Remarks |
| | | Clause | Reference | | | | |
| 5. | MATERIAL | | | | | | |
| 5 | Steel | 5.1 to 5.3 | IS 7285 (Part 2) | S | One | Each cast/ heat | The cylinder manufacturer shall obtain certificates of cast (heat) analysis of steel. |
| | | 5.4, 5.5 | IS 7285 (Part 2) | --- | Each Batch | | |
| 6.7, 6.8.2 | Material for neck ring and foot ring | 6.7, 6.8.2 (As per design/ drawing) | IS 7285 (Part 2) | S | Two | Each consignment | No further testing is necessary if the consignment is received with Test Certificate. |
| 6 | DESIGN | | | | | | |
| 6.6 | Neck Design | 6.6.1, 6.6.2 | IS 7285 (Part 2) | R | Each cylinder | | --- |
| | Valve Fittings | 6.6.3 | IS 7285 (Part 2) | R | Each cylinder | | |
| 6.7 | Foot Ring | 6.7 | IS 7285 (Part 2) | R | Each cylinder | | |
| 6.8 | Neck Ring and Cap | 6.8 | IS 7285 (Part 2) | R | Each cylinder | | |
| 7 | MANUFACTURE | | | | | | |
| 7.1 | General | 7.1 | IS 7285 (Part 2) | R | Each cylinder | | --- |
| 7.2 | Wall thickness | 7.2 | IS 7285 (Part 2) | R | Each cylinder | | |

| | | | | | | |
|-----------|-------------------------|----------------|------------------|---|---|--|
| 7.3 | Surface defects | 7.3 Annex-A | IS 7285 (Part 2) | R | Each cylinder | --- |
| 7.4 | Ultrasonic Examination | 7.4 Annex-B | IS 7285 (Part 2) | R | Each cylinder | The ultrasonic testing shall be certified by the cylinder manufacturer. Every cylinder which has passed the ultrasonic testing shall be stamp marked with the symbol “UT” |
| 7.5 | Out - of - roundness | 7.5 | IS 7285 (Part 2) | R | Each cylinder | --- |
| 7.6 | Mean Diameter | 7.6 | IS 7285 (Part 2) | R | Each cylinder | |
| 7.7 | Straightness | 7.7 | IS 7285 (Part 2) | R | Each cylinder | |
| 7.8 | Verticality | 7.8 | IS 7285 (Part 2) | R | Each cylinder | |
| 7.9 | Stability | 7.9 | IS 7285 (Part 2) | R | Each cylinder | |
| 7.11 | Water Capacity | 7.11 | IS 7285 (Part 2) | R | Each cylinder | |
| 9 | TYPE APPROVAL PROCEDURE | | | | | |
| 9.2.2.b.1 | Hydraulic Bursting Test | 10.5 | IS 7285 (Part 2) | R | As per clause 9.2.2.(b) of IS 7285 (Part 2) | Each new design of cylinder as well as any change in design as per the details given in clause 9.1 of IS 7285 (Part 2) shall be subjected to prototype testing. If the results are satisfactory type approval certificate shall be issued as per clause 9.3 of IS 7285 (Part 2). |
| 9.2.2.b.2 | Tensile Test | 10.2 | IS 7285 (Part 2) | R | | |
| | Impact Test | 10.3 | IS 7285 (Part 2) | R | | |
| | Bend Test | 10.4 | IS 7285 (Part 2) | R | | |

| | | | | | | |
|--------|--|------------------|------------------|---|---|--|
| 9.2.3 | Pressure Cycling Test | 9.2.3 | IS 7285 (Part 2) | R | As per clause 9.2.2.(b) of IS 7285 (Part 2) | Each new design of cylinder as well as any change in design as per the details given in clause 9.1 of IS 7285 (Part 2) shall be subjected to prototype testing. If the results are satisfactory type approval certificate shall be issued as per clause 9.3 of IS 7285 (Part 2). |
| 9.2.4 | Base Check (for cylinder Made from Tube or Made from Continuously Cast Billets) | 9.2.4 | IS 7285 (Part 2) | R | | |
| 9.2.5 | Sulphide Stress Cracking Resistance Test | 9.2.5 9.2.5.1 | IS 7285 (Part 2) | R | | |
| 10 | BATCH TESTS | | | | | |
| 10.1.3 | Tensile Test | 10.2 | IS 7285 (Part 2) | R | As per clause 10.1.3 of IS 7285 (Part 2) | Each new design of cylinder as well as any change in design as per the details given in clause 9.1 of IS 7285 (Part 2) shall be subjected to batch tests for prototype testing. |
| | Impact Test | 10.3 | IS 7285 (Part 2) | R | | |
| | Bend Test | 10.4 | IS 7285 (Part 2) | R | | |
| | Hydraulic Bursting Test | 10.5 | IS 7285 (Part 2) | R | | |
| 10.6 | Pressure Cycling Test for CNG/Bio-CNG Cylinders | 10.6 | IS 7285 (Part 2) | R | One cylinder | |
| 11 | TEST ON EVERY CYLINDER | | | | | |
| 11.2 | Hydrostatic Stretch Test | 11.2 | IS 7285 (Part 2) | R | Each cylinder | --- |
| 11.3 | Hardness Test | 11.3 | IS 7285 (Part 2) | R | Each cylinder | |
| 11.4 | Leakage Test (Pneumatic) | 11.4 | IS 7285 (Part 2) | R | Each cylinder | |
| 11.5 | Water Capacity Check | 7.11 | IS 7285 (Part 2) | R | Each cylinder | |

| | | | | | | |
|----|--------------------------|----|------------------|----|---------------|-----|
| 12 | Colour Identification | 12 | IS 7285 (Part 2) | R | Each cylinder | --- |
| 14 | Cylinder Marking | 14 | IS 7285 (Part 2) | -- | Each cylinder | |
| 17 | Preparation for despatch | 17 | IS 7285 (Part 2) | -- | Each cylinder | |

Note-1: Sub-contracting is permitted to a laboratory recognized by the Bureau or Government laboratories empanelled by the Bureau.

Note-2: The control unit and levels of control given in column 3 are obligatory in nature to which the licensee shall comply with.

ANNEX D

Possible Tests in a day

- i) Wall thickness and other dimensions/requirements as per approved drawing
- ii) Surface defects (Cl. 7.3)
- iii) Ultrasonic examination (Cl. 7.4)
- iv) Hardness Test (Cl. 11.3)
- v) Tensile Test (Cl. 10.2)
- vi) Bend test (Cl. 10.4)
- vii) Impact Test (Cl. 10.3)
- viii) Water Capacity (Cl. 11.5)
- ix) Hydrostatic Stretch Test (Cl. 11.2)
- x) Leakage Test (Cl. 11.4)
- xi) Hydraulic Bursting Test (Cl. 10.5)

ANNEX E**Scope of the Licence**

| | |
|---|--|
| Licence is granted to use Standard Mark as per IS 7285 (Part 2):2017 with the following scope: | |
| Name of the product | REFILLABLE SEAMLESS STEEL GAS CYLINDERS - QUENCHED AND TEMPERED STEEL CYLINDERS WITH TENSILE STRENGTH LESS THAN 1 100 MPa (112 kgf/mm ²) |
| Type | Material Water Capacity (litre) Diameter (mm) Wall thickness (mm) Working Pressure (bar or kgf/cm ²) Test Pressure (bar or kgf/cm ²) Bottom Profile Gas application |
| Any Other Aspect required as per Standard | PESO approved drawing number and approval number |