

PRODUCT MANUAL FOR REFILLABLE SEAMLESS STEEL GAS CYLINDERS NORMALIZED STEEL CYLINDERS ACCORDING TO IS 7285 (Part 1):2018

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure coherence of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification licence/certificate.

1.	Product	:	IS 7285 (Part 1):2018
	Title	:	REFILLABLE SEAMLESS STEEL GAS CYLINDERS - NORMALIZED STEEL CYLINDERS
	No. of amendments	:	1
2.	Sampling Guidelines		
a)	Raw material	:	Steel - Clause 5 of IS 7285 (Part 1)
b)	Grouping Guidelines	•	Each variety of Cylinders shall be tested for GoL/CSoL. [Please see clause 9.1 of IS 7285 (Part 1) also].
c)	Sample Size	:	As per clause 9.2 of IS 7285 (Part 1)
3.	List of Test Equipment	:	Please refer Annex - A
4.	Scheme of Inspection and Testing	•	Please refer <u>Annex - B</u>
5.	Possible tests in a day	:	Please refer Annex - C
6.	Scope of the Licence	:	Please refer Annex - D

BUREAU OF INDIAN STANDARDS

Manak Bhawan, 9, Bahadur Shah Zafar Marg, New Delhi – 110002

ANNEX A

List Of Test Equipment

Major test equipment required to test as per the Indian Standard

Sl. No.	Tests used in with Clause	Reference	Test Equipment		
2100	Test	Clause No.	-		
1	Depth of Concave bottom	Clause 6.4	Depth Gauge		
2	Neck threads	Clause 6.8	Thread inspection gauges		
3	Valve Fitting	Clause 6.6.3	Torque Wrench		
4	Wall Thickness	Clause 7.2	Ultrasonic Thickness Gauge		
5	Surface Defects	Clause 7.3	Ultrasonic Thickness Gauge		
6	Out Of Roundness	Clause 7.4	Vernier Calliper or Outside Micrometre or Set of Outside Calliper and Steel Rule		
7	Mean Diameter	Clause 7.5	Pi tape		
			Outside Calliper with Steel Rule		
			Micrometre		
8	Straightness	Clause 7.6	Feeler Gauge		
			Steel Rule/Straight Edge		
			Steel Rule/Straight Edge		
9	Verticality	Clause 7.7	Fixture for measuring Verticality		
			Feeler Gauge		
			Steel Rule/Straight Edge		
10	Stability	Clause 7.8	Vernier Calliper		
			Scale		
11	Water Capacity	Clause 7.10	Digital Electronic Balance		
12	Hydraulic Bursting Test	Clause 9.2.3	Pressure Gauge		
			Test Fluid Reservoir		
			Tank for measurement of fluids		
			Pressure/Time curve recorder		
			Vent or air release valve		
			Test well		
			High Pressure Pump		
13	Pressure cycling Test	Clause 9.2.4	Pressure Gauge		
			Temperature Sensor		
			Non-Corrosive Liquid		
			Pressure cycling test set up		
			Stop Watch		
14	Base Check	Clause 9.2.5	Magnifying Glass		
15	Tensile Test	Clause 10.2	Universal Testing Machine		
			Vernier Calliper		
			Micrometre		

PM/ IS 7285 (Part 1)/ 1/ Jan 2019

16	Impact Test	Clause 10.3	Impact testing Machine		
			Deep Freezer/Dry ice		
			Thermometer– Digital / Glass type		
			Profile Projector/Go-No Go gauges		
17	Bend Test and flattening test	Clause 10.4	Universal Testing Machine		
18	Hydrostatic Stretch Test	Clause 11.2	Overflow		
			Hydraulic Line Valve		
		Water Jacket	Water Supply		
		Method	Jacket Filling Valve		
			Air Bleed Valve		
			Pump		
			Relief device		
			Drain		
			Calibrated Burette		
			Priming Valve		
			Pressure Gauge		
		Non- Water Jacket Method	Weighing Balance – Electronic Water Tank		
			Bleed Valve		
			Pressure Gauge		
			Pump		
19	Hardness test	Clause 11.3	Weighing Balance Electronic Hardness Testing Machine (Brinell or		
19	Trainiess test	Clause 11.5	Hardness Testing Machine (Brinell or Rockwell)		
20	Leakage Test	Clause 11.4	Pressure Gauge		
			Tank with Lighting Arrangement		

The above list is indicative only and may not be treated as exhaustive.

ANNEX B

Scheme Of Inspection And Testing

- **1. LABORATORY** A laboratory shall be maintained which shall be suitably equipped (as per the requirement given in column 2 of Table 1) and staffed, where different tests given in the specification shall be carried out in accordance with the methods given in the specification.
- **1.1** The manufacturer shall prepare a calibration plan for the test equipments. The following equipments shall be calibrated at a frequency shown against each and records kept:
- **1.1.1** Tensile Testing Machine Once in a year
- **1.1.2** Impact Testing Machine Once in a year
- 1.1.3 Pressure Gauges At least once in a month
- **1.1.4** Pyrometer used for heat treatment furnace Once in six months
- **2. TEST RECORDS** The manufacturer shall maintain test records for the tests carried out to establish conformity. Records of all the tests made at the cylinder manufacturer's work shall be kept for the life time of the cylinder and copies of test certificates shall be forwarded to the purchaser of the cylinder and the inspecting authority.
- **3. LABELLING AND MARKING** As per the requirements of IS 7285 (Part 1):2018.
- **4. BATCH** For the purpose of this scheme, quantity of upto 200 cylinders plus cylinders for destructive testing of the same nominal diameter, thickness and design, made successively from the same steel and subjected to the same heat treatment for the same duration of time shall constitute a Batch.
- **4.1** The identity of each batch shall be maintained. Each batch conforming to all the requirements shall be accompanied by a Certificate in accordance with clause 12 of IS 7285 (Part 1).
- **5. LEVELS OF CONTROL** The tests as indicated in column 1 of Table 1 and the levels of control in column 3 of Table 1, shall be carried out on the whole production of the factory which is covered by this plan and appropriate records maintained in accordance with paragraph 2 above.
- **6. HEAT TREATMENT** The heat treatment of cylinders shall be done as per clause 5.3 of IS 7285 (Part 1). The cylinders shall be punched with serial number before heat treatment to maintain traceability throughout the manufacturing process.
- **6.1** Adequate care shall be taken to ensure the consistency of heat treatment cycle. The deviation of temperature shall be within the specified temperature range. In case the temperature goes outside the specified limits, furnace shall be stopped and all such cylinders shall be segregated. Heat treatment shall be resumed only after attaining the requisite temperature and the furnace temperature is maintained between the specified limits. The complete records of heat treatment cycle and interruptions of cycle shall be maintained.

7. INSPECTION AND TESTING/ RE-TESTS

- **7.1** In order to ensure that the cylinders are in compliance with IS 7285 (Part 1), they shall be subjected to Inspection and Testing in accordance with clause 8 of IS 7285 (Part 1).
- **7.2** In the event of failure of cylinders in meeting the requirements, procedure in accordance with clause **7.9.1** of IS 7285 (Part 1) shall be followed for retesting/re-heat treatment.
- **8. REJECTIONS** Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

TABLE 1

	(1)		(2)	(3)		
	Test D	etails		Test equipment	Levels of Control		
Cl.	Requirement		Γest Methods Clause/ Reference	requirement R: required (or) S: Sub-contracting permitted	No. of Sample	Frequency	Remarks
5.	MATERIAL						
5	Steel	5.1 5.2	IS 7285 (Part 1)	S	One	Each cast/ heat	The cylinder manufacturer shall obtain certificates of cast (heat) analysis of steel.
		5.3 5.4	IS 7285 (Part 1)		Each	Batch	
6.7, 6.8.2	Material for neck ring and foot ring	6.7 6.8.2 (As pe	IS 7285 (Part 1) r design/ drawing)	S	Two	Each consignment	No further testing is necessary if the consignment is received with Test Certificate.
6	DESIGN	1 \ 1			1	1	
6.6	Neck Design	6.6.1 6.6.2	IS 7285 (Part1)	R	Each cyl	inder	
	Valve Fittings	6.6.3	IS 7285(Part 1)	R	Each cyl	inder	
6.7	Foot Ring	6.7	IS 7285 (Part 1)	R	Each cyl	inder	
6.8	Neck Ring and Cap	6.8	IS 7285 (Part 1)	R	Each cyl	inder	
7	MANUFACTURE				•		
7.1	General	7.1	IS7285(Part 1)	R	Each cyl	inder	
7.2	Wall thickness	7.2	IS 7285 (Part 1)	R	Each cyl	inder	
7.3	Surface defects	7.3 Annex-	IS 7285 (Part 1) A	R	Each cyl	inder	

7.4	Out - of - roundness	7.4	IS 7285 (Part 1)	R	Each cylinder	
7.5	Mean Diameter	7.5	IS 7285 (Part 1)	R	Each cylinder	
7.6	Straightness	7.6	IS 7285 (Part 1)	R	Each cylinder	
7.7	Verticality	7.7	IS 7285 (Part 1)	R	Each cylinder	
7.8	Stability	7.8	IS 7285 (Part 1)	R	Each cylinder	
7.10	Water Capacity	7.10	IS 7285 (Part 1)	R	Each cylinder	
7.11 11.1(e)	Neck Thread	6.8 6.6	IS 7285 (Part 1)	R	Each cylinder	
9	TYPE APPROVAL	L PROC	EDURE			,
9.2.3	Hydraulic Bursting Test	9.2.3	IS 7285 (Part 1)	R	As per clause 9.2.2(b) of IS 7285 (Part 1)	Each new design of cylinder as well as any change in design as per the details given in
9.2.4	Pressure Cycling Test	9.2.4	IS 7285 (Part 1)	R	, , ,	clause 9.1 of IS 7285 (Part 1) shall be subjected to prototype testing. If the results are satisfactory type approval certificate shall be issued as per clause 9.3 of IS 7285 (Part 1).
9.2.5	Base Check	9.2.5	IS 7285 (Part 1)	R		
10	BATCH TESTS					
	Tensile Test	10.2	IS 7285 (Part 1)	R	As per clause 10.1.3 of IS 7285 (Part 1)	Each new design of cylinder as well as any change in design as per the details given in
10.1.3	Impact Test	10.3	IS 7285 (Part 1)	R	15 7203 (Fait 1)	clause 9.1 of IS 7285 (Part 1) shall be
	Bend Test	10.4.1	IS 7285 (Part 1)	R		subjected to batch tests for prototype testing.
	Flattening Test	10.4.2	IS 7285 (Part 1)			
	Ring-Flattening Test	10.4.3	IS 7285 (Part 1)			
	Tensile Test Impact Test Bend Test Flattening Test Ring-Flattening	10.3 10.4.1 10.4.2	IS 7285 (Part 1) IS 7285 (Part 1) IS 7285 (Part 1)	R	As per clause 10.1.3 of IS 7285 (Part 1)	Each new design of cylinder a change in design as per the de

11	TEST ON EVERY CYLINDER								
11.2	Hydrostatic Stretch Test	11.2	IS 7285 (Part 1)	R	Each cylinder				
11.3	Hardness Test	11.3	IS 7285 (Part 1)	R	Each cylinder				
11.4	Leakage Test	11.4	IS 7285 (Part 1)	R	Each cylinder				
11.5	Water Capacity Check	7.10	IS 7285 (Part 1)	R	Each cylinder				
13	Colour Identification	13	IS 7285 (Part 1)	R	Each cylinder				
14	Cylinder Marking	14	IS 7285 (Part 1)		Each cylinder				
17	Preparation for despatch	17	IS 7285 (Part 1)		Each cylinder				

Note-1: Sub-contracting is permitted to a laboratory recognized by the Bureau or Government laboratories empanelled by the Bureau.

Note-2: The control unit and levels of control given in column 3 are obligatory in nature to which the licensee shall comply with.

ANNEX C

Possible Tests in a day

- Wall thickness and other dimensions/requirements as per approved drawing i)
- Surface defects ii)
- iii) Hardness Test
- iv) Tensile Test
- Bend test and Flattening test v)
- vi)
- vii)
- Impact Test
 Water Capacity
 Hydrostatic Stretch Test viii)
- Leakage Test ix)
- Hydraulic Bursting Test x)

ANNEX D

Scope of the Licence

Licence is granted to use Standard Mark as per IS 7285 (Part 1):2018 with the following scope:						
Name of the product	REFILLABLE SEAMLESS STEEL GAS CYLINDERS - NORMALIZED STEEL CYLINDERS					
Туре	Material Water Capacity (litre) Diameter (mm) Wall thickness (mm) Working Pressure (bar or kgf/cm²) Test Pressure (bar or kgf/cm²) Bottom Profile Gas application					
Any Other Aspect required as per Standard	PESO approved drawing number and approval number					